

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION  
 © COPYRIGHT - By - TE CONNECTIVITY ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
CM	00	T2		REVISED PER ECR-15-006687	26OCT2015	NK	NL

△ MATERIAL: CONNECTOR - NYLON UL94V-2 (RED).  
 CONTACTS - 0.30[.012] THICK COPPER ALLOY  
 0.00076[.000030] GOLD THK OR 0.00008[.000003] MIN THK  
 GOLD FLASH OVER 0.00068[.000027] THK PALLADIUM NICKEL,  
 PER TE CONNECTIVITY'S DISCRETION. IN CONTACT  
 AREA WITH BRIGHT TIN-LEAD FOR 641229-2 THRU  
 2-641229-4, MATTE WHISKER MITIGATED TIN FOR  
 3-641229-2 THRU 5-641229-4 OVER NICKEL UNDERPLATE.

2 CONTACTS ACCEPT 22 AWG WIRE WITH 2.41[.095] MAX  
 INSULATION DIAMETER.

3 CONTACTS MUST ACCEPT 1.14±0.03 [.045±.001] SQUARE  
 POST AND REMAIN LOCKED IN POSITION.

△ IDENTIFICATION NUMBER FOR LAST CIRCUIT MAY  
 NOT APPEAR ON ALL ASSEMBLIES.

5 DIMENSIONS IN BRACKETS ARE IN INCHES.

6 HOUSING FEATURES ARE: FEED-THRU WITH LOCKING  
 RAMP.

△ OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

95.10	[3.744]	24	5-641229-4
91.14	[3.588]	23	5-641229-3
87.17	[3.432]	22	5-641229-2
83.21	[3.276]	21	5-641229-1
79.25	[3.120]	20	5-641229-0
75.29	[2.964]	19	4-641229-9
71.32	[2.808]	18	4-641229-8
67.36	[2.652]	17	4-641229-7
63.40	[2.496]	16	4-641229-6
59.44	[2.340]	15	4-641229-5
55.47	[2.184]	14	4-641229-4
51.51	[2.028]	13	4-641229-3
47.55	[1.872]	12	4-641229-2
43.59	[1.716]	11	4-641229-1
39.62	[1.560]	10	4-641229-0
35.66	[1.404]	9	3-641229-9
31.70	[1.248]	8	3-641229-8
27.74	[1.092]	7	3-641229-7
23.77	[.936]	6	3-641229-6
19.81	[.780]	5	3-641229-5
15.85	[.624]	4	3-641229-4
11.89	[.468]	3	3-641229-3
7.92	[.312]	2	3-641229-2
95.10	[3.744]	24	<del>2-641229-4</del>
91.14	[3.588]	23	<del>2-641229-3</del>
87.17	[3.432]	22	<del>2-641229-2</del>
83.21	[3.276]	21	<del>2-641229-1</del>
79.25	[3.120]	20	<del>2-641229-0</del>
75.29	[2.964]	19	<del>1-641229-9</del>
71.32	[2.808]	18	<del>1-641229-8</del>
67.36	[2.652]	17	<del>1-641229-7</del>
63.40	[2.496]	16	<del>1-641229-6</del>
59.44	[2.340]	15	<del>1-641229-5</del>
55.47	[2.184]	14	<del>1-641229-4</del>
51.51	[2.028]	13	<del>1-641229-3</del>
47.55	[1.872]	12	<del>1-641229-2</del>
43.59	[1.716]	11	<del>1-641229-1</del>
39.62	[1.560]	10	<del>1-641229-0</del>
35.66	[1.404]	9	<del>641229-9</del>
31.70	[1.248]	8	<del>641229-8</del>
27.74	[1.092]	7	<del>641229-7</del>
23.77	[.936]	6	<del>641229-6</del>
19.81	[.780]	5	<del>641229-5</del>
15.85	[.624]	4	<del>641229-4</del>
11.89	[.468]	3	<del>641229-3</del>
7.92	[.312]	2	<del>641229-2</del>
DIM A		NO OF CIRCUITS	PART NO

DIMENSIONS:		TOLERANCES UNLESS OTHERWISE SPECIFIED:		DWN		TE Connectivity	
mm	[INCHES]	0 PLC	± -	J. HUFFMAN	08 MAR 95	MTA-156 CONNECTOR ASSEMBLY, 22 AWG, STANDARD	
		1 PLC	± -	R. SWING	08 MAR 95		
		2 PLC	± -	APVD		RESTRICTED TO	
		3 PLC	± 0.13 [.005]	D. CLARK		CAGE CODE	
		4 PLC	± -	PRODUCT SPEC		DRAWING NO	
		ANGLES	± 0° 30'	APPLICATION SPEC		SCALE	
MATERIAL	△ 1	FINISH	△ 1	108-1051		SHEET	
				114-1020		1 OF 1	
				WEIGHT		REV	
				CUSTOMER DRAWING		T2	

1471-9 (3/11)

Downloaded From [Onevac.com](http://Onevac.com)

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)