



| | | | | | | | | | | | |
|---------------|---------------|---------------|---------------|----|---------------|----------------|----------------|----------------|----------------|-------|----------|
| 1 & 100 | 2.900 [73.66] | 2.290 [58.17] | 2.450 [62.23] | 49 | 2.825 [71.76] | 5.650 [143.51] | 5.190 [131.83] | 5.890 [149.61] | 6.050 [153.67] | 200 | 534180-8 |
| 1 & 96 | 2.800 [71.12] | 2.190 [55.63] | 2.350 [59.69] | 47 | 2.725 [69.22] | 5.450 [138.43] | 4.990 [126.75] | 5.690 [144.53] | 5.850 [148.59] | 192 | 534180-7 |
| 1 & 90 | 2.650 [67.31] | 2.040 [51.82] | 2.200 [55.88] | 44 | 2.575 [65.41] | 5.150 [130.81] | 4.690 [119.13] | 5.390 [136.91] | 5.550 [140.97] | 180 | 534180-6 |
| 1 & 86 | 2.550 [64.77] | 1.940 [49.28] | 2.100 [53.34] | 42 | 2.475 [62.87] | 4.950 [125.73] | 4.490 [114.05] | 5.190 [131.83] | 5.350 [135.89] | 172 | 534180-5 |
| 1 & 80 | 2.400 [60.96] | 1.790 [45.47] | 1.950 [49.53] | 39 | 2.325 [58.46] | 4.650 [118.11] | 4.190 [106.43] | 4.890 [124.21] | 5.050 [128.27] | 160 | 534180-4 |
| 1 & 76 | 2.300 [58.42] | 1.690 [42.93] | 1.850 [46.99] | 37 | 2.225 [56.52] | 4.450 [113.03] | 3.990 [101.35] | 4.690 [119.13] | 4.850 [123.19] | 152 | 534180-3 |
| 1 & 70 | 2.150 [54.61] | 1.540 [39.12] | 1.700 [43.18] | 34 | 2.075 [52.71] | 4.150 [105.41] | 3.690 [93.73] | 4.390 [111.51] | 4.550 [115.57] | 140 | 534180-2 |
| 1 & 66 | 2.050 [52.07] | 1.440 [36.58] | 1.600 [40.64] | 32 | 1.975 [50.17] | 3.950 [100.33] | 3.490 [88.65] | 4.190 [106.43] | 4.350 [110.49] | 132 | 534180-1 |
| CAVITY IDENT. | I | H | G | F | E | D | C | B | A | POSN. | PART NO. |

- CONNECTOR MEETS ALL APPLICABLE REQUIREMENTS OF MIL-C-55302.
- AMP, AMP PART NO. & DATE CODE MARKED IN THIS APPROXIMATE AREA.
- NUMBERS INDICATING END POSITIONS MARKED THIS SIDE ONLY.
- MINIMUM PAD LENGTH ON CIRCUIT BOARD.
- CONTACT FINISH: .000050 [0.0013] GOLD IN CONTACT AREA, TIN-LEAD ON CONTACT TAILS, ALL OVER NICKEL UNDERPLATE.
- HOUSING MATERIAL: LIQUID CRYSTAL POLYMER PER MIL-M-24519, GLCP-30F; COLOR: GRAY

THIS DRAWING IS A CONTROLLED DOCUMENT AND THE USER REPRESENTS THAT IT IS SUBJECT TO CHANGE AND THE CONTROLLING ENGINEERING DEPARTMENT SHALL BE CONTACTED FOR THE LATEST REVISION.

| | | | |
|-------------|--|------------------|--------------|
| DIMENSIONS: | TOLERANCES UNLESS OTHERWISE SPECIFIED: | DATE | 5-2-95 |
| 0 PLC ± | 1 PLC ± | CHK | T. ALEXANDER |
| 2 PLC ± | 3 PLC ± | APVD | D. GUTTER |
| 4 PLC ± | ANGLES ± | NAME | D. GUTTER |
| MATERIAL | FINISH | PRODUCT SPEC | |
| | | APPLICATION SPEC | |
| | | WEIGHT | |
| | | CUSTOMER DRAWING | |

AMP Incorporated
 Harrisburg, PA 17105-3608

PIN HEADER ASSEMBLY,
 EXTENDED MINI-BOX,
 CARD EXTENDER

SIZE: A1 CAGE CODE: 00779 DRAWING NO: C-534180
 SCALE: 4:1 SHEET 1 OF 1 REV F

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)