



ELECTRICAL	MECHANICAL	ENVIRONMENTAL	HOUSING	MATERIAL	FINISH												
Nominal Impedance (Ohms) <u>50</u>	Interface Dimensions MIL-STD-348, Fig. 310.2	Temperature Rating <u>-65°C TO 125°C</u>	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	PASSIVATE PER QQ-P-35													
Frequency Range (GHz) DC to <u>18.0</u>	Recommended Mating Torque <u>N/A</u>	Vibration MIL-STD-202, Method 204, Condition D	DIELECTRIC PTFE FLUOROCARBON PER ASTM-D-1457	N/A													
Volt Rating (VRMS MAX) @ Sea Level <u>335</u>	Mating Characteristics: Insertion (MAX Lbs) <u>2.0</u>	Shock MIL-STD-202, Method 213, Condition I	CENTER CONTACT BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204													
VSWR <u>1.05 + .005 f(GHz)</u>	Withdrawal (MIN Oz) <u>1.0</u>	Thermal Shock MIL-STD-202, Method 107, Condition B	COMPONENT														
Insertion Loss (dB MAX) <u>.03 √f(GHz)</u>	Force to Engage and Disengage (In/Lbs MAX) <u>2.0</u>	Moisture Resistance MIL-STD-202, Method 106, Except Vibration	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON	<table border="1"> <tr> <td>DRAWN BY</td> <td>MC</td> <td>DATE</td> <td>5-17-88</td> </tr> <tr> <td>CHECKED BY</td> <td>JM</td> <td>DATE</td> <td>6-30-88</td> </tr> <tr> <td>APPD BY</td> <td>FZ</td> <td>DATE</td> <td>8-11-88</td> </tr> </table>		DRAWN BY	MC	DATE	5-17-88	CHECKED BY	JM	DATE	6-30-88	APPD BY	FZ	DATE	8-11-88
DRAWN BY	MC	DATE	5-17-88														
CHECKED BY	JM	DATE	6-30-88														
APPD BY	FZ	DATE	8-11-88														
RF Leakage (dB MIN) <u>-(60-f(GHz))</u>	Center Contact Captivation: Axial (Lbs) <u>6.0 Lbs</u>	Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray	FRAC. ± 1/64	<table border="1"> <tr> <td colspan="2">AMP Incorporated</td> </tr> <tr> <td colspan="2">140 Fourth Avenue</td> </tr> <tr> <td colspan="2">Waltham, MA 02451-7599</td> </tr> </table>		AMP Incorporated		140 Fourth Avenue		Waltham, MA 02451-7599							
AMP Incorporated																	
140 Fourth Avenue																	
Waltham, MA 02451-7599																	
Corona, 70,000 Ft (VRMS MIN) <u>250</u>	Radial (In/Oz) <u>4.0 Inch-Ounces</u>		DEC. ± .005	<table border="1"> <tr> <td colspan="2">TITLE "SMA" FLANGE MOUNT JACK RECEPTACLE CAPTURED CENTER CONTACT TAB TERM (M83517/1-31004)</td> </tr> <tr> <td>SIZE</td> <td>CODE IDENT NO.</td> <td>2052-8006-92</td> <td>REV</td> </tr> <tr> <td>B</td> <td>26805</td> <td></td> <td>01,1</td> </tr> </table>		TITLE "SMA" FLANGE MOUNT JACK RECEPTACLE CAPTURED CENTER CONTACT TAB TERM (M83517/1-31004)		SIZE	CODE IDENT NO.	2052-8006-92	REV	B	26805		01,1		
TITLE "SMA" FLANGE MOUNT JACK RECEPTACLE CAPTURED CENTER CONTACT TAB TERM (M83517/1-31004)																	
SIZE	CODE IDENT NO.	2052-8006-92	REV														
B	26805		01,1														
Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level <u>1000</u>	Cable Retention: Axial Force (Lbs) <u>N/A</u>		ANGLES ± °	<table border="1"> <tr> <td>SCALE</td> <td>5:1</td> <td>SHEET 1 OF 1</td> </tr> </table>		SCALE	5:1	SHEET 1 OF 1									
SCALE	5:1	SHEET 1 OF 1															
Contact Resistance (Milliohms MAX): Center Contact <u>3.0</u>	Torque (In/Oz) <u>N/A</u>		NO. AP. <u>N/A</u>														
Outer Contact <u>2.0</u>	Weight (Grams) <u>2.2</u>																
Cable to Housing <u>N/A</u>																	
RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) <u>670</u>																	
I.R.(Megohms MIN) <u>10,000</u>																	
.XXX = in XX.X = mm (REF)			THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF AMP INTERCONNECT DIVISION AND SHALL NOT BE REPRODUCED OR COPIED OR USED IN WHOLE OR IN PART AS THE BASIS FOR THE MANUFACTURE OR SALE OF ITEM(S) WITHOUT WRITTEN PERMISSION.														

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)