

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION - N/A .  
 © COPYRIGHT N/A By - ALL RIGHTS RESERVED.

REVISIONS				
P	LTR	DESCRIPTION	DATE	APVD
B		REV PER ECO 17-001528	08APR08	CT DM

1 FINISH: PLATED GOLD .000050 [0.00127] MIN THK PER ASTM-B488 OVER NICKEL .000050 [0.00127] MIN THK PER QQ-N-290.

2 .015 TO .030 HIGH GOTHIC "A" STAMPED .001-.002 DEEP. RADIAL LOCATION OPTIONAL.

MAT'L: PHOS BRONZE OR BERYLLIUM COPPER  
 FINISH: NICKELPLATED PER QQ-N-290

RETENTION CLIP

SOCKET BODY  
 MAT'L; COPPER ALLOY  
 FINISH: 1

4-40UNC-2A

R.005 [0.13] MAX TYP 2

R.005 MAX [0.13]

.050 [1.27] MAX UNTHREADED

.34 [8.64]  
 .32 [8.13]

.463 [11.76]  
 .447 [11.35]

.080 MIN [2.03]

.059 [1.50]  
 .049 [1.24]

.113 [2.87]  
 .103 [2.62]

.890 REF [22.60]

.203 MIN [5.16]



.125±.010 [3.17±0.25]

POINT OF PLATING THICKNESS MEASUREMENT

.190 [4.83]  
 .180 [4.57]  
 FLATS

.245 [6.22] DIA  
 .235 [5.97] DIA

1757682-1  
 PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN A.H.ANDERSON 05-APR-05	 TE Connectivity	
DIMENSIONS: INCHES		CHK D.MILLER 05-APR-05		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD D.MILLER 05-APR-05	NAME ASSEMBLY, SOCKET CONTACT POWER VIII, THREADED	
 0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± .005 [0.13] 4 PLC ± - ANGLES ± -		PRODUCT SPEC -	SIZE A2	CAGE CODE 00779
MATERIAL SEE CALLOUTS		FINISH SEE CALLOUTS	WEIGHT 0.000000	DRAWING NO 1757682
		CUSTOMER DRAWING	SCALE 10:1	SHEET 1 of 1
			RESTRICTED TO -	REV B

1471-9 (1/15)

Downloaded From [Onevac.com](http://Onevac.com)

1757682

A

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)