



Pos. (極位)	A	B	C	COLOR (色)	PART NO. (型番)
3	8.5	2	5.0	BLUE (青)	4- -3
7	18.5	6	15.0		2- -7
5	13.5	4	10.0		2- -5
3	8.5	2	5.0		2- -3
2	6.0	1	2.5	BLACK (黒)	2- -2
20	51.0	19	47.5		2- -0
18	46.0	17	42.5		1- -8
17	43.5	16	40.0		1- -7
16	41.0	15	37.5		1- -6
15	38.5	14	35.0		1- -5
14	36.0	13	32.5		1- -4
13	33.5	12	30.0		1- -3
12	31.0	11	27.5		1- -2
11	28.5	10	25.0		1- -1
10	26.0	9	22.5		1- -0
9	23.5	8	20		-9
8	21.0	7	17.5		-8
7	18.5	6	15		-7
6	16.0	5	12.5		-6
5	13.5	4	10		-5
4	11.0	3	7.5		-4
3	8.5	2	5		-3
2	6.0	1	2.5	NATURAL (自然色)	172520 -2

- 注:
- 使用端子は型番 172781
172782
 - 通用製品規格: 108-5163
 - 取扱説明書: IS-207J
-208J
- △ カット端: 0.4 最大
 △ 成形上必要は溝 (オプション)
 △ AMP-台湾のみの製造品

- NOTES:
- APPLICABLE CONTACT: 172781
172782
 - PRODUCT SPEC: 108-5163
 - INSTRUCTION SHEET: IS-207J
-208J
- △ CUTTING END: 0.4 MAX.
 △ THIS GROOVE IS OPTIONAL.
 △ PRODUCTION ITEMS OF AMP TAIWAN ONLY.



適合電線範囲 (WIRE RANGE)	絶縁外径 (INSULATION DIA.)	品名 (NAME)
mm (AWG)	mm	ロープロファイルミニヘッダイン 25ピッチ (25 Pitch)
材料 (MATERIAL)	仕上 (FINISH)	(HEADER HOUSING, LOW PROFILE MINI AMP-IN 25 PITCH)
6/6 ナイロン (UL94-0)		
DR. S. Kato	DE	SIZE LOC 番号 (NO.)
CHK. M. Aoki	APP. N. Oishi	A3 J C-172520
G2 REVISED PER ECO-11-005030	RK HMR	尺 (SCALE) REV. SHEET
LTR 変更 (REVISION RECORD)	DR. CHK. (DATE)	10-1 G2

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)