

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
E		ECR-09-007414	02JUN2009	KG	DW
F		ECR-17-001574	11APR2017	KG	DW

1. USE WITH FERRULE ASSEMBLY KIT P/N 1588908-2 (125um), OR 1588908-1 (126um). QUANTITY OF 4 REQUIRED. FERRULE MUST BE PC-POLISHED DURING FIBER TERMINATION FOR BEST PERFORMANCE.

2. PROTECTIVE LABEL APPLIED AFTER FINAL CLEAN ROOM TEST TO PREVENT OPTICAL CAVITY CONTAMINATION. REMOVE ONLY WHEN READY TO ASSEMBLE.

3. SINGLEMODE IDENTIFIER

4. FOR USE AT BOTH 1310 AND 1550nm WAVELENGTHS.

The drawing shows three views of the insert assembly:

- Top View:** Shows four fiber ports labeled A2, A1, B2, and B1. A callout '3' points to a small circular feature at the top.
- Side View:** Shows the assembly with dimensions: $\varnothing 13.34$ REF (outer diameter), $\varnothing 14.1$ REF (inner diameter), and 18.1 REF (length).
- Perspective View:** Shows the assembly from an angled view, with a callout '2' pointing to a protective label on the side. The fiber ports are labeled A1, B2, and B1. Below the view is the text "SCALE 4:1".

1515740-1

PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN E. HOPKINS 08OCT2002

CHK D. WERTMAN 08OCT2002

APVD D. WERTMAN 08OCT2002

PRODUCT SPEC -

APPLICATION SPEC -

WEIGHT -

CUSTOMER DRAWING

STE

TE Connectivity

NAME INSERT ASSEMBLY, PRO BEAM JR.,
4x1310/1550nm SM

SIZE CAGE CODE DRAWING NO

A300779 C-1515740

RESTRICTED TO -

SCALE 4:1

SHEET 1 OF 1

REV F

DIMENSIONS:

mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC	±-
1 PLC	±-
2 PLC	±-
3 PLC	±-
4 PLC	±-
ANGLES	±-

MATERIAL STAINLESS ALLOYS & NBR

FINISH N/A

1470-19 (3/13)

Downloaded From Onevac.com

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)