

- ① OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI
- ② OBSOLETE


DO NOT SCALE

DIMENSIONS IN MM.



C.A.D. FILE CODE  
C154717

PART NUMBER	MATERIAL	FINISH	REELING	LOOSE PIECE CREF. ONLY
154717-1	BRASS	NONE	STANDARD	341001-1
① 154717-2	PHOS. BRONZE	NONE	STANDARD	341001-2
154717-3	BRASS	TIN	STANDARD	341001-3
154717-4	PHOS. BRONZE	TIN	STANDARD	341001-4
① 154717-5	PHOS. BRONZE	NONE	STANDARD	341001-5
154717-6	BRASS	PRE-TIN	STANDARD	341001-6
154717-7	PHOS. BRONZE	PRE-TIN	STANDARD	341001-7
① 154717-8	PHOS. BRONZE	SILVER	STANDARD	341001-8
154717-9	BRASS	SILVER	STANDARD	341001-9
<del>1-154717-0</del>	<del>OBSOLETE</del>	<del>OBSOLETE</del>	<del>OBSOLETE</del>	---
1-154717-1	BRASS	NONE	REV. REEL VERSION-1	---
① 1-154717-2	PHOS. BRONZE	NONE	REV. REEL VERSION-2	---
1-154717-3	PHOS. BRONZE	PRE-TIN	STANDARD	---
① 1-154717-4	BRASS	TIN	REV. REEL VERSION-3	---
1-154717-5	PHOS. BRONZE	TIN	REV. REEL VERSION-4	---
① 1-154717-6	PHOS. BRONZE	TIN	STANDARD (SPACE FREE VERSION)	---



WIRE RANGE 2.5 TO 4.0mm<sup>2</sup>

INSULATION RANGE 3.6 TO 4.3mm DIA.

CUSTOMER DWG  
FOR REFERENCE ONLY

RELEASED FOR PUBLICATION  
ORIGINAL 1974

TOLERANCES  
UNLESS OTHERWISE  
STATED  
DEC ± 0.5  
ANGLES ± 1°

DR. D.A.BARRATT

27.11.91

CH. D.TERRY

APP. D.A.BARRATT



TE Connectivity

NAME POSITIVE LOCK RECEPTACLE

AR4	REVISED PER ECR-20-005366	13APR2020	SS	DL	SCALE	LOC	SIZE	DWG.No.	REV	SHEET
AR3	ECR-15-007886	17JUN15	NK	GH	4/1	E	A4	C154717	AR4	1/1
REV	DESCRIPTION	DATE	DWN	APVD						

FORMAT 22/05/85

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)