SPECIFICATION CONTROL DRAWING								55PC4236			
TITLE	THREE CONDUCTOR CABLE, JACKETED, GENERAL PURPOSE, 600 VOLT							11-22-06 Revision		A	
This specification sheet forms a part of the latest issue of Raychem Specifiction 55PC.											
	COMPONE	NT WIRES - 55	5PC0216					DIATION-CROSSL DIFIED ETFE	.INKED,		
				CONST	RUCTION DETAI	_S					
	PART NUMBER	CONDUCTOR	JACKET THICKNESS (in.)		DIAMETER (in.)			WEIGHT (lbs/1000 ft.)			
	<u>1/</u>	SIZE (AWG)	LOWER SPEC LIMIT	TARGET WALL	LOWER SPEC LIMIT	TARGET VALUE	UPPER SPEC LIMIT	TARGET VALUE	UPPER SPE LIMIT	EC .	
	55PC4236-26-*	26	.0055	.0070	.084	.089	.094	5.71	6.16		
	55PC4236-24-*	24	.0055	.0070	.095	.100	.105	7.69	8.21		
	55PC4236-22-*	22	.0055	.0070	.108	.113	.118	10.69	11.28		
	55PC4236-20-*	20	.0060	.0075	.127	.132	.137	15.61	16.30		
	55PC4236-18-* 55PC4236-16-*	18 16	.0060 .0060	.0075	.148 .164	.153 .170	.158 .176	22.65 28.52	23.50 29.53		
CABLE RATINGS AND ADDITIONAL REQUIREMENTS TEMPERATURE RATING: 200°C PART NUMBER: Maximum continuous conductor temperature The "*" in the part numbers above VOLTAGE RATING: 600 volts (rms) at sea level designators with a slash separate DIELECTRIC WITHSTAND: 1500 volts (rms) dash separating the component CROSSLINK VERIFICATION: 300 ± 3°C for 1 hour 1/ Example: AWG 20, red, yellow JACKET COLOR: White preferred white jacket: 55PC4: JACKET ELONGATION AND TENSILE STRENGTH: Elongation, 50% (minimum) Tensile Strength, 5000 lbf/in² (minimum) Tensile Strength, 5000 lbf/in² (minimum)							rating the compo nt wire colors fro low and blue com	nent wire colo m the jacket o ponent wires	ors and a color.		
	Users s Tyco Electronics also r	hould evaluate the eserves the right to	e suitability of this o make changes ir	product for their materials or pro	application. Specific cessing, which do r	cations are subje ot affect compliar	ct to change with nce with any spec	out notice. fication, without not	ification to Buye	r.	
Page 1 of 1	1/ COLORS AND COLOR CODE DESIGNATORS SHALL BE IN ACCORDANCE WITH MIL-STD-681. HOWEVER, DUE TO LENGTH LIMITATIONS OF THE RAYCHEM PART NUMBER, AN ALTERNATIVE COLOR CODE MAY REPLACE MIL-STD-681 COLOR CODE DESIGNATORS. (EXAMPLE: "901/902" MAY BE REPLACED BY "Axxx".) OTHER CODES AND SUFFIXES MAY BE ADDED TO THE PART NUMBER, AS NECESSARY, TO CAPTURE ANY ADDITIONAL REQUIREMENTS IMPOSED BY THE PURCHASE ORDER. DIMENSIONS ARE IN INCHES AND. UNLESS OTHERWISE DESIGNATED, ARE NOMINAL								tyco	Raychem Wire & Cable 501 Oakside Avenue Redwood City, CA 94063-3800	
-	THIS SPECIFICATION SHEET TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BID.									Phone: 1-800-227-8816 Fax: 1-650-361-6297	

Downloaded From Oneyac.com

© 2006 Tyco Electronics Corporation. All rights reserved.

单击下面可查看定价,库存,交付和生命周期等信息

>>TE Connectivity(泰科)