



- NOTES :
- ▲ MATERIALS AND FINISH:
- HOUSING: PA66
 - CONTACTS: BRASS, FINISH: TIN OVER NICKEL UNDERPLATE
2. MUST COMPLY WITH DIRECTIVE 2002/95/EC (ROHS)
 3. WIRE TYPES AND SIZES ACCEPTED
WIRE RANGE: 20AWG~28AWG.
STRIP LENGTH: 5.5mm~6.5mm
 4. PACKAGED IN TRAY.
 5. CURRENT RATING: 4AMP AC150V.
 6. OPERATION TEMPERATURE: -40°C TO +105°C
 7. THIS PART NO. IS THE SAME STRUCTURE AS THE SERIES: 2834085
THE DATASHEET AND MORE DETAILS PLEASE FOLLOW THE SERIES: 2834085

④	③	②	①	NO. OF POSITIONS	PART NO
WIRE PROTECTOR	CONTACT	COVER	HOUSING	A	
21.82	8 POSN	2834085-7			
19.28	7 POSN	2834085-6			
16.74	6 POSN	2834085-5			
14.20	5 POSN	2834085-4			
11.66	4 POSN	2834085-3			
9.12	3 POSN	2834085-2			
6.58	2 POSN	2834085-1			
A					

THIS DRAWING IS A CONTROLLED DOCUMENT.

DATE: 08DEC2015
 NAME: 254 45Entry Screwless Connector
 SIZE: A2
 CODE: 00779
 SCALE: 1:1

REVISIONS

REV	DATE	DESCRIPTION
1	08DEC2015	REVISED TO

TE Connectivity

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)