

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20

ALL RIGHTS RESERVED.

LOC  
JDIST  
-

REVISIONS


変更

P	LTR	DESCRIPTION	ECN	DATE	DWN	APVD
	A2	ADDED -3	ECR-15-017009	20NOV2015	TS	HY

1. INSTRUCTION SHEET ; 411-5933
2. DOUBLE LOCK SHOULD BE SET TO THE PRE-ASSEMBLY POSITION WITHIN THE PLUG HOUSING WHEN SHIPPED TO THE CUSTOMER.
3. APPLICABLE CAP HOUSING PN:1376515-1

1. 取扱説明書: 411-5933
2. ダブルロックは、仮係止状態で出荷される。
3. 嵌合相手型番: 1376515-1

NATURAL	1318620-3
BLACK	1318620-2
BLUE	1318620-1
COLOR	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN N. YASUDA	02SEP99	 TE Connectivity	
DIMENSIONS: 単位: 耗 mm		CHK N. SAI	02SEP99		
TOLERANCES UNLESS OTHERWISE SPECIFIED: 一般公差 一般公差 = ± 0.2		APVD N. SAI	02SEP99		
0-PLC ± 1-PLC ±0.1 2-PLC ±0.01 3-PLC ±0.001 4-PLC ±0.0001 ANGLES ±3'00"		PRODUCT SPEC 製品規格	108-5675		
MATERIAL 材料 PBT		FINISH 仕上 BLACK	APPLICATION SPEC 取付適用規格	114-5250	NAME 名称 025 4P PLUG HOUSING, ANCHOR HEIGHT SENSOR
		WEIGHT 0.65 g	SIZE A3	CAGE CODE 00779	DRAWING NO 番号 C-1318620
		CUSTOMER DRAWING	SCALE 尺度 5:1	SHEET 1	OF 1
					RESTRICTED TO -
					REV A2

1470-19 (3/11)

Downloaded From [Onevac.com](http://Onevac.com)

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)