



NOTES;

- △ TO BE MEASURED WITH IN 2mm FROM □
- △ IN COUPLING WITH THE PLUG HOUSING MATING SATISFIES FUNCTION
- 3 APPLIED CONTACT P/N 1722777, 1722779
- 4 PRODUCT SPEC No. 108-5165
- 5 IN COUPLING WITH THE PLUG HOUSING MATING FORCE 29.4N(3KGf) MAX. WITHOUT REC. CONTACT

- 注;
- △ □ 面より 2mm の範囲で測定
 - △ 相手ハウジングと所定の機能を満たして嵌合できること
 - 3 内接するプラグコンタクト型番 1722777, 1722794
 - 4 製品規格 NO. 108-5165
 - 5 相手ハウジングとの嵌合力は 29.4N(3KGf) 以下 但しプラグコンタクトは含まない

取付寸法 (1/1)
* : I と II 及び III と IV は 0.1 以内の同寸法のこと。

TR	REV	DATE	CHK	DR	REV	DATE	CHK
A				TS	KT	1984	
A		製作成	FILED				
LTR		REVISION RECORDED	0074-94				

Copyright © 1982 All Rights Reserved.		Copyright © 1982 All Rights Reserved.	
REGULATORY ONLINE RATED	REGULATORY ONLINE RATED	REGULATORY ONLINE RATED	REGULATORY ONLINE RATED
INSULATION	INSULATION	INSULATION	INSULATION
ENVIRONMENTAL	ENVIRONMENTAL	ENVIRONMENTAL	ENVIRONMENTAL
DR. T. Shinohara	DR. T. Shinohara	DR. T. Shinohara	DR. T. Shinohara

172513-7	黄 (YELLOW)
-6	灰 (GRAY)
-5	青 (BLUE)
-4	緑 (GREEN)
-3	赤 (RED)
-2	黒 (BLACK)
172513-1	自然色 (NATURAL)
番号 (P/N)	色 (COLOR)

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)