




LOC		DIST		REVISIONS			
P	LTR	DESCRIPTION	DATE	DMN	APVD		
B1		REVISED PER ECO-11-004835	11MAR11	RK	HMR		



MATERIAL: GLASS REINFORCED THERMOPLASTIC RATED 94V-0.

2. COLOR: BLUE

609-6431HD	85.95	(3.384)	64	1-1437022-3
609-5031HD	68.17	(2.684)	50	8-1437021-1
609-4031HD	55.47	(2.184)	40	5-1437021-5
609-3431HD	47.85	(1.884)	34	3-1437021-2
609-2631HD	37.69	(1.484)	26	1-1437021-2
609-2031HD	30.07	(1.184)	20	8-1437020-6
609-1631HD	24.99	(0.984)	16	6-1437020-6
609-1431HD	22.45	(0.884)	14	5-1437020-1
609-1031HD	17.37	(0.684)	10	3-1437020-7
T&B PART NO (REF)	A	NO OF POSN	PART NO	

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm [INCHES]	TOLERANCES UNLESS OTHERWISE SPECIFIED:	DIN W. DABULAS 3/25/83	CHK G. KLEMM 3/25/83	APVD R.R. 3/31/83	NAME
0. PLC ± .01	1. PLC ± .01	TE Connectivity		HEAVY DUTY STRAIN RELIEF FEMALE SOCKET CONNECTOR	
2. PLC ± .01	3. PLC ± .01	APPLIC. SPEC		SIZE: A1	
4. PLC ± .01	ANGLES ± .01	WEIGHT		CAGE CODE: 00779	
MATERIAL	FINISH	CUSTOMER DRAWING		DRAWING NO: 3-1437020-7	
		SCALE: 10:1		SHEET 1 OF 1	

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)