



- CONNECTOR DIMENSIONS ARE PER ARINC 600 SPECIFICATION
- DUST COVER (NOT SHOWN) INSTALLED FOR SHIPPING.
- KEYING SHOWN IN POSITION "01" FOR REFERENCE ONLY. SEE TABLE FOR KEYING POSITION. FOR POSITION "00" KEYING SHIPPED UNASSEMBLED.

COMPONENT	MATERIAL	FINISH
SHELL	DIE CAST ALUMINUM PER ASTM-B-85	CHEMICAL CONVERSION COATING PER MIL-C-5541, CLASS 1A
RETENTION PLATES	ALUMINUM ALLOY PER ASTM-B-209	CHEMICAL CONVERSION COATING PER MIL-C-5541, CLASS 1A
SCREWS AND LOCKWASHERS	STEEL OR STAINLESS STEEL	CHROMATE OVER ZINC OR PASSIVATED
POLARIZING POSTS	ZINC ALLOY PER ASTM-B-86	ELECTROLESS NICKEL PER MIL-C-26074 CLASS 4, GRADE B
POLARIZING POST RETAINING PLATE	ALUMINUM ALLOY PER ASTM-B-209	BLUE ANODIZED PER MIL-A-8625
150, 60 & 34 INSERTS	THERMOSET	-

KEYING POSITION	CONTACTS INCLUDED	PART NUMBER
01	NO CONTACTS INCLUDED	1996034-2
01	MODULE A 208262-3 (SIZE 22 CRIMP PIN CONTACT; QTY=150) MODULE B 208267-2 (SIZE 20 CRIMP SOCKET CONTACT; QTY=60) MODULE C 208267-2 (SIZE 20 CRIMP SOCKET CONTACT; QTY=24) 208270-2 (SIZE 16 CRIMP SOCKET CONTACT; QTY=10)	1996034-1
	CONTACTS INCLUDED	
	NOT INSTALLED	

THIS DRAWING IS A CONTROLLED DOCUMENT. DIMENSIONS: INCHES. TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± .005, 1 PLC ± .004, 2 PLC ± .003, 3 PLC ± .002, 4 PLC ± .001, ANGLES ± .005. MATERIAL: SEE TABLE. FINISH: SEE TABLE. WEIGHT: -. APPLICATION SPEC: A1.00779. CUSTOMER DRAWING. SCALE: 1:1. SHEET: 1 OF 1. REV: A.

APPROVED: K. HOGAN, 4-24-07. Tyco Electronics Corporation, Harrisburg, PA 17105-3608. NAME: PLUG ASSY, SIZE 2, ARINC 600, (150/60/34), RR.

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)