



RECOMMENDED P.C. BOARD HOLE LAYOUT

- 1 "AMP", "CSA", "▼", AND "DATE CODE" WITH .062±.015 HIGH CHARACTERS WHERE SIZE PERMITS.
- 2 HOUSING: 1-70 POSITION SIZES MAY BE PPS, GLASS-FILLED OR PCT, GLASS-FILLED. POSITION SIZES GREATER THAN 70 WILL BE PPS, GLASS-FILLED.
- 3 CONTACT: PHOSPHOR BRONZE.
- 4 CONTACT FINISH: DUPLEX PLATED 0.00076 [.000030] GOLD IN CONTACT AREA, 0.00127-0.00254 [.000050-.000100] BRIGHT TIN-LEAD ON SOLDER TAILS, ALL OVER 0.00127 [.000050] NICKEL.
- 5 THESE DIMENSIONS PERTAIN TO CAVITY CL'S ONLY, NOT TO CONTACT LOCATIONS.
- 6 POINT OF MEASUREMENT FOR PLATING THICKNESS (INSIDE CONTACT BEAMS).
- 7 CSA LOGO INK STAMPED WHITE ON HOUSING.
- 8 CONTACT FINISH: DUPLEX PLATED 0.00076 [.000030] GOLD IN CONTACT AREA, 0.00127-0.00254 [.000050-.000100] MATTE TIN ON SOLDER TAILS, ALL OVER 0.00127 [.000050] NICKEL.
- 9 ROHS 2002/95/EC COMPLIANT.
- 10 RECESSED AREA AROUND MOLD GATE IS OPTIONAL. THIS FEATURE IS ALLOWABLE ON EITHER SIDE OF HOUSING OR MAY NOT BE PRESENT AT ALL.
- 11 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI.

FINISH	B	A	NO OF POSN	PART NUMBER	FINISH	B	A	NO OF POSN	PART NUMBER
			89	180				89	180
			21	44				21	44
			79	160				79	160
			46	94				46	94
			6	14				6	14
			99	200				99	200
			73	148				73	148
			64	130				64	130
			63	128				63	128
			59	120				59	120
			54	110				54	110
			49	100				49	100
			47	96				47	96
			44	90				44	90
			42	86				42	86
			39	80				39	80
			35	72				35	72
			34	70				34	70
			29	60				29	60
			24	50				24	50
			19	40				19	40
			17	36				17	36
			14	30				14	30
			11	24				11	24
			9	20				9	20
			7	16				7	16
			5	12				5	12

THIS DRAWING IS A CONTROLLED DOCUMENT. DWN: K.L.CLOUSER/UTA 3/6/91
CHK: D.SARVER 5/14/91

STE TE Connectivity

RECEPTACLE ASSY, MOD II, DBL ROW, 2.54 X 2.54 [.100 X .100] CL, GUIDE PIN EARS, CLOSED ENTRY.

SIZE: A1 CAGE CODE: 00779 DRAWING NO: 533009 RESTRICTED TO: 533009

WEIGHT: -- SCALE: 6:1 SHEET: 1 OF 1 REV: V5

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)