
# Thermofit Molded Parts Specification Control Drawing Limited Distribution

Part Number: 202A1XX-X-27
Description: Boot, Straight



- 1. All dimensions are in  $\frac{\text{inches}}{[\text{millimeters}]}$
- 2. Dimensions appearing in table are as follows:
  - a As Supplied
  - b After Unrestricted Recovery
- Coating is optional. As supplied dimensions appearing in table are for uncoated parts. When coating is added, entry diameters will be reduced by .06 max.






TABLE OF DIMENSIONS										
PART NUMBER	Н		J		Р	R	JO	w		
	Min	Max	Min	Max	±10%	±10%	Ref	±20%		
	a	ь	a	ь	b	b	ь	ь		
202A132-X-27	1.12 [28,4]	.56 [14,2]	1.12 [28,4]	.26 [6,6]	.91 [23,1]	.35 [8,9]	.26 [6,6]	<u>.07</u> [1,78]		
202A163-X-27	1.68 [42,7]	1.08 [27,4]	1.68 [42,7]	. <u>37</u> [9,4]	1.66 [42,1]	.56 [14,2]	.38 [9,6]	.08 [2,03]		

#### Raychem


RAYCHEM CORPORATION 300 CONSTITUTION DRIVE MENLO PARK, CALIFORNIA 94025 Revision: A
Date: 9/16/98

Part Number: 202A1XX-X-27
Description: Boot, Straight

## Thermofit Molded Parts Specification Control Drawing Limited Distribution

Part Number :	202A1XX-X-27
Description :	Boot, Straight

COMPATABILITY CHART								
MATERIAL DASH NO.	MATERIAL DESCRIPTION	RT SPEC	COATING SLASH NO.	COATING S NO.	COATING DESCRIPTION			
-3	Polyolefin, Semi-rigid	RT-301	/42,/86	S-1017,S-1048	Adhesive			
-4	Polyolefin, Flexible	RT-1304	/42,/86	S-1017,S-1048	Adhesive			
-25	Elastomer, Fluid Resistant	RT-1325	/42; /86	S-1017; S-1048	Adhesive			



THIS DRAWING IS SUBJECT TO CHANGE WITHOUT NOTICE; CONSULT YOUR NEAREST FIELD REPRESENTATIVE FOR CURRENT REVISION

#### Raychem

RAYCHEM CORPORATION 300 CONSTITUTION DRIVE MENLO PARK, CALIFORNIA 94025

Revision : A Date : 9/16/98 Part Number : 202A1XX-X-27

Description : Boot, Straight

CAD FILE MP98145

### 单击下面可查看定价,库存,交付和生命周期等信息

## >>TE Connectivity(泰科)