



REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
01 ₀	RELEASED PER ECN 90-0203-1	1/15/90	<i>PJA</i>

HOUSING	BRASS PER QQ-B-626	GOLD PLATE PER MIL-G-45204 OVER COPPER PLATE PER MIL-C-14550
COUPLING NUT	COMP. 360	
CLAMP NUT		
SLEEVE		
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457, MIL-P-19468, AND FED. SPEC L-P-403	N/A
CENTER CONTACT	BERYLLIUM COPPER PER ASTM B196, ALLOY 173	GOLD PLATE PER MIL-G-45204 OVER COPPER PLATE PER MIL-C-14550
RETAINING RING	BERYLLIUM COPPER PER ASTM B196	N/A
FERRULE	SOFT COPPER ALLOY	GOLD PLATE PER MIL-G-45204 OVER COPPER PLATE PER MIL-C-14550
COMPONENT	MATERIAL	FINISH

CABLE ENTRY DIAMETER MINIMUM	
FERRULE	.098
SLEEVE	.035
CONTACT	.014

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES
TOLERANCE ON
FRAC. DEC. ANGLES
± 1/64 ± .005 ± °

These drawings and specifications are the property of Omni Spectra Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.

DRAWN BY M.CATIZONE DATE 9-9-89
CHECKED BY C.WARD 1/15/90
APP'D BY *PJA* 1/15/90

USE ASS'Y PROCEDURE

408-04711
NO. AP. (50-036)

AMP Incorporated
140 Fourth Avenue
Waltham, MA 02451-7599

AMP

TITLE SMC STRAIGHT CABLE PLUG CRIMP ATTACHMENT

SIZE B	CODE IDENT NO. 26805	5031-5007-09	REV 01 ₀
SCALE 5:1		SHEET 1 OF 1	

- NOTES:
- DESIGNED FOR USE WITH RG178/U AND RG196/U CABLE.
 - CAPTURED CENTER CONTACT

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)