



- ① PINS: 0.00076[0.000030] MINIMUM GOLD IN CONTACT AREA, 0.00381[0.000150] MIN TIN ON SOLDER TAILS, ALL OVER 0.00127[0.000050] MINIMUM NICKEL.
- 2. CUSTOMER TO PROVIDE CARD GUIDANCE SYSTEM.
- ③ DATUMS AND BASIC DIMENSIONS ESTABLISHED BY CUSTOMER.
- 4. CONNECTOR REQUIRES USE OF 2 - SIZE 2M SCREWS FOR FASTENING TO PRINTED CIRCUIT BOARD.
- ⑤ ASSEMBLY KEYED FOR 5 VOLT CARDS.
- ⑥ ASSEMBLY KEYED FOR LOW VOLT CARDS (3.3V).
- ⑦ HOUSING & ORGANIZER: LCP, COLOR; BLACK. PINS: BRASS.

| | | | | |
|---------------------------------|-------------------------------|----------------|-------------|-----------|
| ⑥ | 1,17,34 | ALL OTHER PINS | 36,67 | 5535655-2 |
| | 35,51,68 | OTHER PINS | | |
| ⑤ | 1,17,34 | ALL OTHER PINS | 36,67 | 5535655-1 |
| | 35,51,68 | OTHER PINS | | |
| VOLTAGE KEYING & IDENTIFICATION | 5.0 [0.197] | 4.25 [0.167] | 3.5 [0.138] | PART NO |
| | "L" (PIN LENGTH) AND LOCATION | | | |

| | | | |
|--|--|-------------------------------|---|
| THIS DRAWING IS A CONTROLLED DOCUMENT. | | DWN L VARELA - DOCK5 03-23-05 | Tyco Electronics Corporation Harrisburg, PA 17105-3608 |
| DIMENSIONS: mm [INCHES] | | CHK S BOLASH 03-23-05 | |
| TOLERANCES UNLESS OTHERWISE SPECIFIED: | | APVD M WALMSLEY 03-23-05 | PIN HEADER ASSY, 68 POSN, RAISED HEIGHT, TOP BD MTG, THRU-HOLE, MEMORY CARD |
| 0 PLC ± - | | PRODUCT SPEC | |
| 1 PLC ± - | | APPLICATION SPEC | SIZE CAE CODE DRAWING NO A1 00779 C=5535655 |
| 2 PLC ± 0.13 [005] | | RESTRICTED TO | |
| 3 PLC ± - | | SCALE 4:1 | SHEET 1 OF 1 |
| 4 PLC ± - | | REV 0 | |
| ANGLES ± - | | WEIGHT 8.5 GRAMS | |
| FINISH ① | | CUSTOMER DRAWING | |

**COPYRIGHT 2005
 TYCO ELECTRONICS CORP
 ALL RIGHTS RESERVED**

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)