



REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
01 2	REVISED	T.W. 9/5/96	ICom 9/6/96

ELECTRICAL
Nominal Impedance (Ohms) <u>50</u>
Frequency Range (GHz) DC to <u>18.0</u>
Volt Rating (VRMS MAX) @ Sea Level <u>335</u>
VSWR <u>1.07 + .01 f(GHz)</u>
Insertion Loss (dB MAX) <u>.03 √f(GHz)</u>
RF Leakage (dB MIN) <u>-[60-f(GHz)]</u>
Corona, 70,000 Ft (VRMS MIN) <u>250</u>
Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level <u>1000</u>
Contact Resistance (Milliohms MAX) Center Contact <u>2.0</u> Outer Contact <u>2.0</u> Cable to Housing <u>N/A</u>
RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) <u>670</u>
I.R.(Megohms MIN) <u>10000</u>

MECHANICAL
Interface Dimensions MIL-STD-348A, Fig. 310.2
Recommended Mating Torque <u>7-10 IN LBS</u>
Mating Characteristics: Insertion (MAX Lbs) <u>3.0</u> Withdrawal (MIN Oz) <u>1.0</u>
Force to Engage and Disengage (In-Lbs MAX) <u>2.0</u>
Center Contact Captivation Axial (Lbs) <u>6.0</u> Radial (In-Oz) <u>4.0</u>
Cable Retention Axial Force (Lbs) <u>N/A</u> Torque (In-Oz) <u>N/A</u>
Weight (Grams) <u>1.6</u>

ENVIRONMENTAL
Temperature Rating <u>-65°C to +105°C</u>
Vibration MIL-STD-202, Method 204, Condition D
Shock MIL-STD-202, Method 213, Condition I
Thermal Shock MIL-STD-202, Method 107, Condition A
Moisture Resistance MIL-STD-202, Method 106
Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray
<u>.XXX = in</u> <u>XX.X = mm (REF)</u>

COMPONENT	MATERIAL	FINISH									
HOUSING	STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303	GOLD PLATE PER MIL-G-45204									
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A									
CENTER CONTACT	BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204									
<table border="1"> <tr> <td rowspan="3">UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON FRAC. DEC. ANGLES ± 1/64 ±.005 ± °</td> <td>DRAWN BY <u>JB</u></td> <td>DATE <u>3/31/76</u></td> <td rowspan="3"> </td> <td rowspan="3"> <b>AMP Incorporated</b> 140 Fourth Avenue Waltham, MA 02451-7599         </td> </tr> <tr> <td>CHECKED BY <u>RMF</u></td> <td><u>3/31/76</u></td> </tr> <tr> <td>APPD BY <u>BWC</u></td> <td><u>4/1/76</u></td> </tr> </table>			UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON FRAC. DEC. ANGLES ± 1/64 ±.005 ± °	DRAWN BY <u>JB</u>	DATE <u>3/31/76</u>		<b>AMP Incorporated</b> 140 Fourth Avenue Waltham, MA 02451-7599	CHECKED BY <u>RMF</u>	<u>3/31/76</u>	APPD BY <u>BWC</u>	<u>4/1/76</u>
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON FRAC. DEC. ANGLES ± 1/64 ±.005 ± °	DRAWN BY <u>JB</u>	DATE <u>3/31/76</u>			<b>AMP Incorporated</b> 140 Fourth Avenue Waltham, MA 02451-7599						
	CHECKED BY <u>RMF</u>	<u>3/31/76</u>									
	APPD BY <u>BWC</u>	<u>4/1/76</u>									
TITLE <b>OSM 2 HOLE FLANGE MOUNT JACK RECEPTACLE STRAIGHT TERMINAL</b>											
USE ASS'Y PROCEDURE	NO. AP. <u>N/A</u>										
SIZE <b>B</b>	CODE IDENT NO. <b>26805</b>	<b>2052-5674-00</b>	REV <b>01 2</b>								
SCALE <b>4:1</b>			SHEET 1 OF 1								

CUSTOMER DRAWING AMP PART # 1052901-1 SHEET 1 OF 1 REV A

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)