



RECOMMENDED MOUNTING HOLE

HOUSING		STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303		GOLD PLATE PER MIL-G-45204 OVER NICKEL PLATE PER QQ-N-290	
DIELECTRIC		TFE FLUOROCARBON PER ASTM-D-1457		N/A	
CTR CONTACT		BERYLLIUM COPPER PER ASTM B196, ALLOY C17300, CONDITION H		GOLD PLATE PER MIL-G-45204 OVER COPPER PLATE PER MIL-C-14550	
CONTACT EXT		IRON-NICKEL-COBALT ALLOY PER MIL-I-23011 (KOVAR)		GOLD PLATE PER MIL-G-45204	
METAL GASKET		SAE C12L14 STEEL		SILVER PLATE PER QQ-S-365	
HERMETIC SEAL		GLASS BEAD		N/A	
COMPONENT		MATERIAL		FINISH	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON		DRAWN BY M.Y. DATE 4-18-91		AMP Incorporated	
FRAC. DEC. ANGLES ± 1/64 ± .005 ± 1°		CHECKED BY C.W. 4-18-91		140 Fourth Avenue	
These drawings and specifications are the property of Omni Spectra Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.		APPD BY <i>YDD</i> 4-18-91		Waltham, MA 02451-7599	
USE ASS'Y PROCEDURE		TITLE OSM PANEL FEEDTHRU JACK RECEPTACLE HERMETICALLY SEALED		REV 01 ₀	
408-04847		SIZE B		CODE IDENT NO. 26805	
NO. AP. (20-600)		SCALE 5:1		2058-5119-00	
				SHEET 1 OF 1	

ELECTRICAL	MECHANICAL	ENVIRONMENTAL
Nominal Impedance (Ohms) 50	Interface Dimensions MIL-STD-348A	Temperature Rating -65°C To +125°C
Frequency Range (GHz) DC - 26.5	FIG 310.2	Vibration - MIL-STD-202, Method 204, Condition D, 20G's
Volt Rating (VRMS MAX) 335 @ Sea Level	Recommended Mating	Shock - MIL-STD-202, Method 213, Condition I
VSWR 1.04 + (.009 F(GHz))	Torque N/A	Thermal Shock MIL-STD-202, Method 107, Condition B
Insertion Loss (dB MAX) .05√F(GHz)	Mating Characteristics:	Except High Temp 115°C
RF Leakage (dB MIN) -(100 - F(GHz))	Insertion (MAX Lbs) 3.0	Moisture Resistance - MIL-STD-202, Method 106
Corona, 70,000 Ft (VRMS MIN) 333	Withdrawal (MIN Oz) 1.0	Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray
Dielectric Withstanding Voltage (VRMS MIN) 1000 @ Sea Level	Force To Engage (In/Lbs MAX) 2.0	Leak Test - MIL-STD-202, Method 112, Condition C, Procedure I, 1 x 10 CC/Sec
Contact Resistance (Milliohms MAX)	Force To Disengage (In/Lbs MAX) 2.0	
Center Contact 10.0	Center Contact Captivation	
Outer Contact 2.0	Axial 6.0 Lbs	
RF High Potential (VRMS MIN @ 5 MHz) 670 @ Sea Level	Radial N/A	
I.R.(Megohms) 5000	Weight (Grams) T.B.D.	

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)