### SPECIFICATION CONTROL DRAWING

5026S1614

**CHEMINAX** 

.063

.079

50 OHM, AWG 26, 7 STRANDS OF AWG 34, COAXIAL CABLE, OUTER SPACE USE

3-7-08 Date С Revision


THIS SPECIFICATION SHEET FORMS A PART OF THE LATEST ISSUE OF RAYCHEM SPECIFICATION 1200.

### CONSTRUCTION DETAILS

**ELECTRICAL CHARACTERISTICS** 

DIMENSIONS ARE NOMINAL VALUES IN INCHES UNLESS OTHERWISE DESIGNATED

CHARACTERISTIC IMPEDANCE 50 ± 2 ohms, Method A CAPACITANCE 26.7 pF/ft. (nominal) VELOCITY OF PROPAGATION 76% (nominal)



SHIELD

**JACKET** 

Radiation-Crosslinked,

Modified ETFE

AWG 38,

Tin-Coated Copper

## ADDITIONAL REQUIREMENTS

**ELECTRICAL** 

CONDUCTOR RESISTANCE 43.9 ohms/1000 ft. (nominal)

10,000 megohms (minimum) INSULATION RESISTANCE

for 1000 ft.

JACKET FLAWS

SPARK TEST 1.0 kV (rms) IMPULSE TEST 6.0 kV (peak)

VOLTAGE WITHSTAND (DIELECTRIC) 1000 volts (rms) (minimum)

**ENVIRONMENTAL** 

**FLAMMABILITY** Method B **HEAT SHOCK** 225°C

LOW TEMPERATURE-COLD BEND -55°C/2.25 inch mandrel

**VOLTAGE WITHSTAND** 

(Post Environmental) 1000 volts (rms), 1 minute

**PHYSICAL** 

INSULATION (DIELECTRIC)

(Prior to Cabling)

**ELONGATION** 50% (minimum) 1000 lbf/in2 (minimum) TENSILE STRENGTH

**ELONGATION** 50% (minimum) TENSILE STRENGTH 5000 lbf/in2 (minimum) JACKET THICKNESS .008 inch (nominal) SHIELD COVERAGE 90% (minimum)

WEIGHT 5.5 lbs/1000 ft. (nominal)

**OUTER SPACE REQUIREMENTS** Outer jacket color will be white (designated by a "-9" appended RADIATION RESISTANCE

500 megarads/2.25 inch mandrel

VACUUM STABILITY

TOTAL MASS LOSS (TML) 1.00% (maximum) **VOLATILE CONDENSABLE** 0.10% (maximum)

MATERIAL (VCM)

Users should evaluate the suitability of this product for their application. Specifications are subject to change without notice. Tyco Electronics also reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to Buyer.

The TE logo, Tyco Electronics, Cheminax, Raychem and Rayfoam are trademarks.



requirements imposed by the purchase order.

to the part number, e.g. 5026S1614-9) unless otherwise

the part number, as necessary, to capture any additional

Designate outer jacket color with a dash number in accordance

with MIL-STD-681. Other codes and suffixes may be added to

Raychem Wire & Cable 501 Oakside Avenue Redwood City, California 94063-3800 1-800-227-8816 Fax: 1-650-361-6297

THIS SPECIFICATION SHEET TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BID.

## 单击下面可查看定价,库存,交付和生命周期等信息

# >>TE Connectivity(泰科)