








LOC	DIST	REVISIONS					
DS	-	P	LYR	DESCRIPTION	DATE	DWN	APVD
		A		RELEASED	09.JUL'07	DG	JK
		B		REVISED (ECR-09-008790)	16.JUL'09	KT	HG



- NOTE
- 본 부품은 ES91500-00을 만족할 것.
  - <상대 CONNECTOR P/N: 91206-82000 (TE P/N: 1897260)와 ASS'Y 상태에서 만족할 것>
  - 각 단차 상발력은 TE Production Spec. 108-10042(4.2성)을 따를 것.
  - 다음 사용환경을 만족할 것.
    - 내열성: -40 ~ 150 °C
    - 내유성: 상기온도 인진오일에서 내유성 확보할 것.
    - 내진성: 30G
  - 가능성 유해한 흄, 균열, 결함 등이 없을 것.
  - APPLIED TERMINAL P/N: SEE TABLE 1
  - MATING TAB P/N: SEE TABLE 2
  - 지시하지 않은 ROUND는 지면 R로 할 것.
  - DRAFT ANGLE MAX. 0.5°
  - FLASH=MAX 0.2, WARPAGE=MAX 0.2
  - 표시하지 않은 일반 공차는 ES02514-00의 2급을 따를 것.
  - 단차 시험시 SEAL PROTECTOR(P/N:208338-1)를 반드시 사용할 것.

< TABLE 1 >

TYPE	PART NO.	WIRE SIZE(mm <sup>2</sup> /AWG)	INSULATION DIA.(mm)	CONDUCTOR STRANDING (NUMBER X AWG)
III+	66100-8	0.85 / 18	1.778	19 X 30

< TABLE 2 >

TYPE	PART NO.	WIRE SIZE(mm <sup>2</sup> /AWG)	INSULATION DIA.(mm)	CONDUCTOR STRANDING (NUMBER X AWG)
III+	66098-8	0.85 / 18	1.778	19 X 30

QTY	FINISH/COLOR	MATERIAL	DESCRIPTION	PART NO.	Q'TY	1897263-1	ASSY P/N
5	BLACK	PA66-GF15	COUPLING RING	1897265-2	1		
4	BLACK	PA66-GF30	COVER HOUSING	1897262-2	1		
3	RED	SILICON RUBBER	FAMILY SEAL	1897905-6	1		
2	RED	SILICON RUBBER	INNER SEAL	1897906-6	1		
1	BLACK	PA66-GF30	PLUG HOUSING	1897264-2	1		

DIMENSIONS: (mm) 		TO BRANDS UNLESS OTHERWISE SPECIFIED 0 PLC ± 1 PLC ± 2 PLC ± 3 PLC ± 4 DEC. ANGLES ±		DWN: KT JANG CHK: JW JANG APVD: HJ OH		Tyco Electronics AMP KOREA Kyungson, Korea	
MATERIAL: SEE TABLE		FINISH: -		PRODUCT SPEC: APPLICATION SPEC:		NAME: SIZE: A2 CAGE CODE: 00779 DRAWING NO: C=1897263 RESTRICTED TO: -	
CUSTOMER DRAWING				SCALE: 1:1		SHEET: 1 OF 1 REV: B	

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)