

TECHNICAL DATA SHEET

TE Document: TTDS-094 Issue: 3 Date: March 2014



KEY FEATURES

- Zero Halogen
- Excellent Resistance to Burning
 UL94 HB rated
- UV stabilised material
 On black marker with white legends
- Resistant to key fluids, including those used in Energy, Oil refineries, Aviation and Military (defined by RW-2538)
- Ten sizes for cable diameters 1.0 to 19.0mm (0.04 to 0.75 inches)
- Secure grip for positive fixing to cable
- Applicator wands available for easy marker installation
- Applicator has a patented slit to prevent over-expansion of the marker during application
- The high elasticity of the marker enables material to be installed without damaging the substrate

APPLICATIONS

- Post termination cable identification
- Identification of small wires and cables, including optical fibres.
- Ideally suited for use in Energy projects including power stations, oil refineries and offshore platforms.

STD and STB Markers

STD and STB markers are individual snap on markers used to identify wires and small cables permanently. STD markers are white and yellow. STB markers are colour coded.

Markers are side-entry installed using an applicator wand, so allowing identification after termination and/or installation. These markers have an expanding profile which enable markers to accommodate a wide range of wire and small cable sizes. Markers are supplied chevron cut to ensure the legend remains aligned.

Manufactured using a zero halogen polyoxymethylene (POM) compound, this marker lends itself to installations where a permanent solution is required. Ideally suited for use in Energy projects including power stations, oil refineries and offshore platforms.

TEMPERATURE RATING

Operating Temperature Range -40°C to 106°C (-40°F to 223°F)

ENVIRONMENTAL

No Halogens, Sulphur, Nitrogen, Phosphorus and Cadmium sources above trace level

Information and a downloadable declaration covering RoHS and REACH compliance can be found at the 'TE Product Compliance Support Centre':

http://www.te.com/en/resources/product-compliance.html


SPECIFICATIONS / APPROVALS

TE Connectivity Standard

• RW-2538


PART DESCRIPTION

STD - Standard marker



— Product family

STB - Color coded marker



Where possible, TE have tested product as a finished item, including the print. Operational tests are followed by an assessment of mark adherence to validate fit form and function. Further details can be found in TE standard RW-2538.



TECHNICAL DATA SHEET

TE Document: TTDS-094

Issue: Date: 3 March 2014

STD and STB Markers

ORDERING INFORMATION

| | White/ Yellow marker size code | Color marker size code | Cable dia mm | Cable diameter mm inches | | Packed box |
|--|--------------------------------------|------------------------------|-----------------|-----------------------------|---------|--|
| | STD 01 | STB 01 | 1.00 – 1.40 | 0.040 - 0.055 | Brown | 10 wands with 30 identical markers |
| | STD 02 | STB 02 | 1.40 – 1.80 | 0.055 – 0.071 | Grey | 10 wands with 30 identical markers |
| | STD 03 | STB 03 | 1.90 – 2.65 | 0.075 – 0.104 | Green | 10 wands with 30 identical markers |
| | STD 05 | STB 05 | 2.30 - 3.00 | 0.091 – 0.118 | Natural | 10 wands with 30 identical markers |
| | STD 06 | STB 06 | 2.60 - 3.50 | 0.102 – 0.138 | Red | 10 wands with 30 identical markers |
| | STD 09 | STB 09 | 3.25 – 4.50 | 0.128 – 0.177 | Blue | 10 wands with 30 identical markers |
| | STD 12 | STB 12 | 4.50 - 6.00 | 0.177 – 0.236 | Yellow | 10 wands with 30 identical markers |
| | STD 15 | STB 15 | 5.80 - 8.50 | 0.228 – 0.335 | Orange | 50 identical markers. Applicator available separately* |
| | STD 17 | STB 17 | 8.50 – 11.50 | 0.335 – 0.452 | Orange | 50 identical markers. Applicator available separately* |
| | STD 21 | STB 21 | 11.00 – 15.50 | 0.433 – 0.610 | Grey | 50 identical markers. Applicator available separately* |
| | STD 24 | STB 24 | 15.00 – 19.00 | 0.590 – 0.750 | Grey | 50 identical markers. Applicator available separately* |
| | | | | | | |

APPLICATORS*

| Order code | Marker size | Color of applicator | Number of applicators per pack |
|---------------------|-------------|---------------------|--------------------------------|
| STD15-Applicator 15 | | Orange | 5 |
| STD17-Applicator | 17 | Orange | 5 |
| STD21-Applicator | 21 | Grey | 2 |
| STD24-Applicator | 24 | Grey | 2 |

STD COLOR CODE

3

- Y Yellow W
 - vv

Black

STB COLOR CODE Legend Marker color Ink color Legend Marker color Ink color Legend Marker color 4 0 Black White Yellow Black 8 Grey 1 Brown White 5 Green White 9 White 6 2 Red White Blue White

Violet

7

White

Orange

Ink color

Black

Black

White



TECHNICAL DATA SHEET

| TTDS-094 | TE Document: |
|------------|--------------|
| 3 | Issue: |
| March 2014 | Date: |

STD and STB Markers

LEGEND CODE

| Legend | Code | Legend | Code | Legend | Code |
|--------|------|--------|-------|--------|--------|
| 0 | 0 | J | J | / | Slash |
| 1 | 1 | К | К | Earth | Earth |
| 2 | 2 | L | L | Blank | Blank |
| 3 | 3 | М | Μ | : | Colon |
| 4 | 4 | Ν | Ν | = | Equals |
| 5 | 5 | 0 | 0 | | Dot |
| 6 | 6 | Р | Р | | |
| 7 | 7 | Q | Q | | |
| 8 | 8 | R | R | | |
| 9 | 9 | S | S | | |
| А | А | т | т | | |
| В | В | U | U | | |
| С | С | V | V | | |
| D | D | W | W | | |
| Е | E | Х | Х | | |
| F | F | Y | Y | | |
| G | G | Z | Z | | |
| Н | н | + | Plus | | |
| I. | I | - | Minus | | |

While TE has made every reasonable effort to ensure the accuracy of the information in this document, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.

design specifications.
 *Trademarks. TE Connectivity, TE connectivity (logo), and TE (logo) are trademarks. Other logos, product and/or company names may be trademarks of their respective owners.

单击下面可查看定价,库存,交付和生命周期等信息

>>TE Connectivity(泰科)