



1. THIS PLUG IS DESIGNED TO CONFORM TO THE LATEST ISSUE OF MIL-C-24308
 2. MAX WIRE INSUL. TO BE USED WITH THIS PLUG IS .054 DIA.
 3. METAL RETENTION CLIPS ARE INCLUDED IN INSERTS
 4. PACKAGE MARKED M 24308/4-334F
 5. THIS PLUG WILL ACCEPT SIZE 22 PIN CONTACT M 24308/13 OR AMP # 204370
- AMP PART NO. MARKED ON CONNECTOR REPRESENTS KIT NUMBER WITH CONTACTS

THIS DRAWING IS A CONTROLLED DOCUMENT.

DESIGNED BY	DATE	12-3-97
DRAWN BY	DATE	1-28-98
CHECKED BY	DATE	1-28-98
APPROVED BY	DATE	
PROJECT NO.	0.000000	
REV	A1	
DESCRIPTION	AMPLITE PLUG FOR PIN CONTACTS HI-DENSITY D CONNECTOR SIZE 6, 104 POSN., SERIES 90 WITH FLOAT BUSHINGS	
QUANTITY	1	
DATE	3-27-16	
BY	CT	
APP	DM	

STE TE Connectivity

CUSTOMER DRAWING

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)