1 MATES WITH HOUSING 480285.
2 PARTS COMPLY WITH AMP SOLDERABILITY SPEC 109-11-3.
3 DIMENSION SHOWN REPRESENT PRODUCT IN DRY CONDITION. ADDITIONAL 2% GROWTH DUE TO END USE LOCATION MOISTURE ABSORPTION MAY OCCUR AND SHOULD BE ACCOUNTED FOR.





RECOMMENDED LAYOUT FOR .125 THICK P.C. BOARD

1. MATES WITH HOUSING 480285.
2. PARTS COMPLY WITH AMP SOLDERABILITY SPEC. NO. 109-11-3

Unpublished copy not to be reproduced nor published without written permission of AMP Incorporated

LTR	REVISION RECORD	DR	CHK	DATE
K1	RESTORED	BKD	RS	3/20/85
K	REV. PER M-7375	SS	GM	8-27-84
J	[illegible] M-7285	DAS	DH	4/11/83
H	ADDED NOTE 3, M-6694	MF	DH	4-30-81
G	REV. TAIL LENGTH M-5334	MF	DH	3-24-79
F	REVISED M-4161	MF	DH	3-7-77
E	ECN M-3871	RRN	DH	3-10-76
D	ECN M-3452	GV	RRF	9/18/74
C	ECN M-3156	BC	MW	9/17/73
B	SUPERSEDES REDRAWN ADDED COLORS	[illegible]	[illegible]	6/26/73

MILLIMETER 350219

REQUIRED PER ASSEMBLY	DESCRIPTION

350219-1	NYLON-NATURAL	copper alloy-PRE-TIN
ASSEMBLY NO.	HSG. MATL & COLOR	PIN MATL & FINISH

© 1973 BY AMP INCORPORATED. ALL RIGHTS RESERVED. AMP PRODUCTS COVERED BY PATENTS AND/OR PATENTS PENDING.

CUSTOMER COPY REFERENCE ONLY

DR 9. Eckman 6-13-73
CHK 6-14-73
DE
APP Emil P. Kowalczyk 6/14/73

MATERIAL AND FINISH: SEE TABLE

WIRE-RANGE-INSULATION: — | —
TOLERANCE EXCEPT AS NOTED ±.015 ±1°0'
SCALE —
CLASS —
TYPE —
LOC CM B NO 350219 REV M1

NAME 10 CIRCUIT MATE-N-LOK P.C. BOARD HEADER

TE Connectivity

M1	REVISED PER ECR-21-117185	PJ / VS	20OCT2021
M	OBSOLETE -2 PER ECN CM-2709	NJG / RS	6-26-92
L	OBSOLETE 1-1, 1-2, 2-1, 2-2, 3-1, 3-2, 4-1, 4-2, 5-1, 5-2, 6-1, 6-2, 7-1, 7-2, 8-1, 8-2, 9-1, 9-2 CM 4/13	KW / RS	4-19-86

DIMENSIONS IN INCHES. DO NOT SCALE PRINT.

PRINT 53

AMP 1253 REV 11/65

Downloaded From Oneyac.com

单击下面可查看定价，库存，交付和生命周期等信息

>>TE Connectivity(泰科)

Downloaded From Oneyac.com