



SECTION A-A

- 1. TIN PER MIL-T-10727 OR TIN LEAD 0.00254 [.000100] MIN THK.
- 2. GOLD PER MIL-G-45204, TYPE II, 0.00076 [.000030] MIN THK OVER NICKEL PER QQ-N-290 0.00028 [.000011] MIN THK ON CONTACT AREA.
- 3. GOLD FLASH PER MIL-G-45204, TYPE II, 0.13µm [.000005] MIN THK. OVER NICKEL PLATE PER QQ-N-290 0.51µm-1.52µm [.000020-.000060] EXT THK.
- 4. RECOMMENDED HOLE SIZE, PLATED OR UNPLATED:
 MACHINE INSERTION: 1.32 $\begin{matrix} +0.03 \\ -0.05 \end{matrix}$ [.052 $\begin{matrix} +.001 \\ -.002 \end{matrix}$]
 HAND INSERTION: 1.32 $\begin{matrix} +0.10 \\ -0.00 \end{matrix}$ [.052 $\begin{matrix} +.004 \\ -.000 \end{matrix}$]
- 5. APPLICATION TOOL PART NUMBER:
 MACHINE NO. 682127-3
 INSERTION HEAD NO. 682039-2
- 6. TO INSURE PROPER SPRING TENSION DO NOT EXCEED A 0.10 [.004] DIFFERENCE IN PIN DIA WHEN CHANGING TO A SMALLER PIN.
- 7. BOTTOM PLUG KNOCKOUT TOOL PART NUMBER 69729 WITH TIP PART NUMBER 69728.
- 8. OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

8	OBSOLETE	CLOSED	0.36-0.66 [.014-.026]	TIN 1	TIN 1	50863-8
	OBSOLETE	KNOCKOUT		GOLD 3	GOLD 2	50863-7
OBSOLETE	OPEN	TIN 1		50863-6		
OBSOLETE	CLOSED	TIN 1		50863-5		
OBSOLETE	KNOCKOUT	GOLD 3		50863-4		
OBSOLETE	OPEN	TIN 1		50863-3		
				GOLD 2	50863-1	
				TIN 1	50863	
				GOLD 3		
	BOTTOM TYPE	RECOMMENDED PIN DIA 6	EYELET	SPRING	PART NO	

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN	R. TALLEY	4-8-91
CHK	S. ROBERTSON	8-22-91
APVD	R. MILLER	8-5-91

STE TE Connectivity

MINIATURE SPRING SOCKET ASSEMBLY SERIES 2

SIZE	A2	CAGE CODE	00779	DRAWING NO	G-50863	RESTRICTED TO	-
SCALE	20:1	SHEET	1 of 1	REV	Z4		

CUSTOMER DRAWING

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)