



1. THE CONTACT SURFACES OF THE TERMINALS ARE COATED WITH LUBRICANT.
2. MATERIAL: HOUSING & COVER - THERMOPLASTIC, BLACK. TERMINALS - PHOS BRONZE PLATED WITH EITHER .000030 MINIMUM GOLD PLATE OR GOLD FLASH OVER PALLADIUM NICKEL PLATE, .000030 MIN TOTAL ON MATING SURFACE. GOLD FLASH PLATED ON TERMINATING SIDE. .000050 MINIMUM NICKEL UNDERPLATE OVER ENTIRE TERMINAL.
3. COVER SHOWN LOOSE BUT SHIPPED ASSEMBLED.
4. WIRE RANGE: 26 AWG SOLID THRU 30 AWG SOLID AND 28 AWG STRANDED RIBBON CABLE.
5. ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY UNLESS OTHERWISE SPECIFIED.
6. FLAT CABLE SHALL BE FURNISHED BY CUSTOMER.
7. MATING FACE CONSISTS OF TWO ROWS OF TERMINALS ON .085 CENTERS, TERMINATING SIDE CONSISTS OF TERMINALS ON .100 CENTERS FOR AN EFFECTIVE .050 TERMINATION.

B. FOR MORE INFORMATION REFER TO AMP PRODUCT SPECIFICATION 108-8078 & APPLICATION SPEC 114-6030.

REVISED FOR PRODUCTION		REVISIONS	
GP	00	DATE	11/17/83
H		BY	BM1 VM

THIS DRAWING IS A CONTROLLED DOCUMENT		DATE	
DIMENSIONS INCHES		REV	15/04/87
ORANGE SHIELDS		BY	W. MILLIENES
PRODUCT SPEC		DATE	15/04/87
APPLICATION SPEC		BY Type Electronics	
CUSTOMER DRAWING		Toronto, Ontario, Canada	
AS SHOWN		DESCRIPTION PART NUMBER	
A2100779		RECEPTACLE ASSEMBLY, 38 POSITION	
553601		SCREEN LOCK, LOW PROFILE, SLEW CLAMP LATCH	
SCALE 2:1		SHEET 1 OF 1	

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)