
# SPECIFICATION CONTROL DRAWING WIRE, RADIATION-CROSSLINKED, MODIFIED ETFE-INSULATED, MEDIUM WEIGHT, GENERAL PURPOSE, 600 VOLT This specification sheet forms a part of the latest issue of Raychem Specification 55PC.



CONSTRUCTION DETAILS													
PART NUMBER 1/	WIRE SIZE (AWG)	CONDUCTOR STRANDING (number x AWG)	CONDUCTOR DIAMETER (in.)			FINISHED WIRE							
						MAXIMUM RESISTANCE	DIAMETER (in.)			WEIGHT (lbs/1000 ft.)			
			LOWER SPEC LIMIT	TARGET VALUE	UPPER SPEC LIMIT	AT 20°C (ohms/1000 ft.)	LOWER SPEC LIMIT	TARGET VALUE	UPPER SPEC LIMIT	TARGET VALUE	UPPER SPEC LIMIT		
55PC021A-26-*	26	19 x 38	.0188	.0194	.0200	57.5	.0342	.0356	.0372	1.45	1.58		

#### WIRE RATINGS AND ADDITIONAL REQUIREMENTS

TEMPERATURE RATING: 200°C

Maximum continuous conductor temperature VOLTAGE RATING: 600 volts (rms) at sea level

COLOR: White preferred

CONDUCTOR BREAK STRENGTH (Finished Wire): 20 lbs (minimum)

CROSSLINK VERIFICATION: 300 ± 3°C for 1 hour

IDENTIFICATION AND COLOR STRIPING DURABILITY:

125 cycles (250 strokes) (minimum). 500 g weight.

INSULATION ELONGATION AND TENSILE STRENGTH:

Total Insulation,

Elongation, 50% (minimum)

Tensile Strength, 5000 lbf/in<sup>2</sup> (minimum)

INSULATION FLAWS:

Spark Test, 3.0 kV (rms)

Impulse Dielectric Test, 8.0 kV (peak)

INSULATION THICKNESS: .008 in. (nominal) total insulation

SHRINKAGE:  $230 \pm 3^{\circ}$ C for 1 hour, 0.125 inch (maximum) in 12 inches.

VOLTAGE WITHSTAND TEST (Post Environmental): 2500 volts (rms)

#### PART NUMBER:

The "\*" in the part number above shall be replaced by a color code designator,

1/ Example: AWG 26, white: 55PC021A-26-9

AWG 26, white with black stripe: 55PC021A-26-90

Users should evaluate the suitability of this product for their application. Specifications are subject to change without notice.  Tyco Electronics also reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to Buyer.								
1/ COLORS AND COLOR CODE DESIGNATORS SHALL BE IN ACCORDANCE WITH MIL-STD-681. OTHER CODES AND SUFFIXES MAY BE ADDED TO THE PART NUMBER, AS NECESSARY, TO CAPTURE ANY ADDITIONAL REQUIREMENTS IMPOSED BY THE PURCHASE ORDER.								
Page 1 of 1	The TE logo, Tyco Electronics and Raychem are trademarks.		Raychem Wire & Cable 501 Oakside Avenue Redwood City, CA 94063-3800 Phone: 1-800-227-8816 Fax: 1-650-361-6297					
	DIMENSIONS ARE IN INCHES, AND UNLESS OTHERWISE DESIGNATED ARE NOMINAL.							
	THIS SPECIFICATION SHEET TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BID.	Electronics						

### 单击下面可查看定价,库存,交付和生命周期等信息

## >>TE Connectivity(泰科)