

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION 20

© COPYRIGHT 20 TE ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS				
P	LTR	DESCRIPTION	DATE	DWN	APVD	
GP	00	B	REV PER ECO-11-007678	18MAY2011	RG	DO

4X .100

DRILLED HOLE  
 $\varnothing .0453 \pm .001$   
 AFTER PLATING  
 $\varnothing .043 / .037, 10X$

.400 TRACE

.300

.400

CROWN

.500

.410

(.150)

(.300)

5 .020 BOARD STAND-OFF

4X .100

- PART NUMBER CHANGES AND/OR DESIGN CHANGES AFFECTING ITEM INTERCHANGEABILITY REQUIRE PRIOR TE APPROVAL AND AUTHORIZATION BY REVISION TO THIS DRAWING.
- ITEMS PROVIDED TO THIS SPECIFICATION SHALL BE IDENTIFIED ON CONTAINER WITH THE FOLLOWING INFORMATION, PART NUMBER AND DATE CODE OF MANUFACTURE.
- MATERIAL:  
 INSULATOR - POLYESTER, GLASS FILLED, UL94 V-O RATED, COLOR: BLACK  
 MODULE - METAL CASTING  
 CROWN - BeCu  
 CONTACT - BRASS

4. FINISH:  
 INSERT - SILVER PLATED .000200 MIN THK.  
 OVER NICKEL .000040 MIN THK.  
 CROWN - GOLD PLATED .000030 MIN THK.  
 OVER NICKEL .000040 MIN THK.

5 A FIVE POUND (5lb) FORCES REQUIRED TO CORRECTLY SEAT THE CONNECTOR WITH PLATED THRU HOLES LESS THEN  $\varnothing .040$ .

6643232-1  
 PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 18MAY2011 LOVATO/GRZYBOWSKI	TE Connectivity	
DIMENSIONS: INCHES		CHK D.ORRIS		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD 18MAY2011 CHAU/ORRIS	NAME ICCON SOCKET, PARALLEL 10 PIN FOOTPRINT, SOLDER STYLE	
0 PLC ±-		PRODUCT SPEC	-	
1 PLC ±-		APPLICATION SPEC	-	
2 PLC ±-		WEIGHT	-	
3 PLC ±.020		CUSTOMER DRAWING	SCALE 4:1	SHEET 1 OF 1
4 PLC ±-		FINISH	REV B	
ANGLES ±.5		MATERIAL	RESTRICTED TO	
-		SIZE A3	CAGE CODE 00779	DRAWING NO C-6643232

1470-19 (3/11)  
 Downloaded From [Onevac.com](http://Onevac.com)  
 Pro/ENGINEER DRAWING

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)