

	2					1						
LOC	DIST	REVISIONS										
АD	00	Р	LTR		DESCRIPTION		DATE	DWN	APVD			
			D	REVISED PER	ECO-13-002771		22FEB2013	КН	RP			
			E	REVISED PER	ECO-19-009248		JUL20 9	ΑP	SY			

CONTACT AND SHIELD - PHOS BRONZE HOUSING AND CHICKLET - LCP, UL 94V-0, COLOR - BLACK

CONTACT AREA FINISH CONFORMS TO THE REQUIREMENTS

OF TE PRODUCT SPECIFICATION 108-2303; BASED ON TELCORDIA GR-1217-CORE FOR SYSTEM QUALITY

LEVEL III, APPLICATIONS IN CONTROLLED ENVIRONMENTS (CENTRAL OFFICE).

COMPLIANT PIN AREA- 0.5µm MIN MATTE TIN OVER 1.27µm MIN NICKEL. SHIELD I.27µm MIN NICKEL.

3 CONNECTOR MARKED ON EITHER SIDE OF HOUSING WITH PART NUMBER, DATE CODE AND STANDARD IN APPROXIMATE AREA SHOWN.

4 dimension applies to centerline of thru hole.

 $\sqrt{5}$ datums and basic dimensions established by customer.

6. CONTACT AREA LUBRICATED WITH BELLCORE APPROVED LUBRICANT. TECHNICAL REFERENCE: GR-1217-CORE, ISSUE I, NOVEMBER 1995.

 $\overline{27}$ reference application spec 114-13202 for recommended plated THRU HOLE DIAMETER AND PLATING THICKNESSES.

1/8 THE GROUNDS IN EACH COLUMN ARE COMMONED.

9 SHOWN LOGO OR OTHER TE OWNED LOGOS IN APPROXIAMATE AREA.

NTROLLED DOCUMENT.		DWN <u>S.J.MAG</u> Chk W. DAVIS	3 JAN2007	TE Connectivity								
TOLERANCES U OTHERWISE SPEC	NLESS IFIED:	APVD R.PATTEF	27AUG2007 RSON	NAME	R E	ECEPT	ACLE	e asse	MBLY	,		
PLC ±- PLC ±- PLC ±-		PRODUCT SPEC				5 PA	IR,	6 CO -	_UMN			
PLC ±- PLC ±- NGLES	±-	APPLICATION -	SPEC	SIZE	CAGE CODE	DRAWING					REST	RICTED T
INISH - /2	- /2	WEIGHT	-	A 1	00779	C-			0.0557		L	-
<u>/ </u>		CUSTOMER	DRAWING				SCA	6:1	SHEET	0F		^{rev} E

|93422|-

PART NUMBER

单击下面可查看定价,库存,交付和生命周期等信息

>>TE Connectivity(泰科)