

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
B1		ECR-18-013580	30AUG2018	WQR	CW
B2		ECR-19-000492	23JAN2019	AL	CW
C		ECR-19-004179	24APR2019	AL	CW
D		ECR-21-111798	27SEP2021	WQR	CW

NOTES:

- TECHNICAL CHARACTERISTICS:  
INSULATION MATERIAL: PC  
RATED VOLTAGE: 50V  
RATED CURRENT: 5A  
INSULATION RESISTANCE:  $\geq 400M\Omega$   
RATED IMPULSE VOLTAGE: 0.8KV  
POLLUTION DEGREE: 3  
FLAMMABILITY: UL94V-0  
MATING CYCLES: 500 CYCLES  
WIRE RANGE: 0.08~0.52 mm<sup>2</sup> (28~20 AWG)  
CONTACT TYPE: CRIMP CONTACT
- CONTACT NEED TO BE ORDERED SEPARATELY.  
(ORDER No. REFER TO DRAWING: T20700X10XX000)

注释:

- 技术参数:  
绝缘材料: PC  
额定电压: 50V  
额定电流: 5A  
绝缘电阻:  $\geq 400M\Omega$   
额定脉冲电压: 0.8KV  
污染等级: 3  
阻燃等级: UL94V-0  
插拔次数: 500次  
接线范围: 0.08~0.52 mm<sup>2</sup> (28~20 AWG)  
接线类型: 冷压接
- 端子需要单独订购.  
(订货号参考图面: T20700X10XX000)

T2111092101-000	HMN-009-M	HMN-009 MALE MODULE INSERT HMN-009模块公插
-----------------	-----------	---

PART NUMBER  
料号PART DESCRIPTION  
描述

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN 24MAR2015

David Wang

CHK 24MAR2015

Chris Wang

APVD 24MAR2015

Xiang Xu

PRODUCT SPEC

108-137064

APPLICATION SPEC

114-137064

WEIGHT

-

Customer Drawing

NAME

HMN-009-M

SIZE

A3

CAGE CODE

00779

DRAWING NO

G-T2111092101000

RESTRICTED TO

-

SCALE

3:2

SHEET

1 OF 1

REV

D

DIMENSIONS:  
mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC	±-
1 PLC	±-
2 PLC	±-
3 PLC	±-
4 PLC	±-
ANGLES	±-
FINISH	-

MATERIAL

-

-

1470-19 (3/13)

Downloaded From [Oneyac.com](http://Oneyac.com)

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)