



REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
01 <sub>3</sub>	REVISED ECN 97-0358-2	10/27/97	Tubag

ELECTRICAL	MECHANICAL	ENVIRONMENTAL	HOUSING	DIELECTRIC	CENTER CONTACT	COMPONENT	MATERIAL	FINISH	
Nominal Impedance (Ohms) <u>50</u> Frequency Range (GHz) DC to <u>18</u> Volt Rating (VRMS MAX) @ Sea Level <u>335</u> VSWR <u>1.05 + .005f GHz</u> Insertion Loss (dB MAX) <u>.03√f GHz</u> RF Leakage (dB MIN) <u>-[60-f(GHz)]</u> Corona, 70,000 Ft (VRMS MIN) <u>250</u> Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level <u>1000</u> Contact Resistance (Milliohms MAX) Center Contact <u>3.0</u> Outer Contact <u>2.0</u> Cable to Housing <u>N/A</u> RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) <u>670</u> I.R.(Megohms MIN) <u>10,000</u>	Interface Dimensions MIL-STD-348A, Fig. <u>310-2</u> Recommended Mating Torque <u>7-10 in-Lbs</u> Mating Characteristics: Insertion (MAX Lbs) <u>3.0</u> Withdrawal (MIN Oz) <u>1.0</u> Force to Engage and Disengage (In/Lbs MAX) <u>2</u> Center Contact Captivation Axial (Lbs) <u>6.0</u> Radial (In/Oz) <u>4.0</u> Weight (Grams) <u>2.2</u>	Temperature Rating <u>-65°C To +125°C</u> Vibration MIL-STD-202, Method 204, Condition B Shock MIL-STD-202, Method 213, Condition I Thermal Shock MIL-STD-202, Method 107, Condition B, Moisture Resistance MIL-STD-202, Method 106, Except Vibration Shall Be Omitted Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray	STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303	PTFE FLUOROCARBON PER ASTM-D-1457	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H	PASSIVATE PER QQ-P-35	N/A	GOLD PLATE PER MIL-G-45204	
			UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON	DRAWN BY <u>RMK</u>	DATE <u>4-30-69</u>	<b>AMP Incorporated</b> 140 Fourth Avenue Waltham, MA 02451-7599			
			FRAC. DEC. ANGLES <u>± 1/64 ±.005 ± 1°</u>	CHECKED BY <u>PW</u>	<u>5/14/69</u>				
			These drawings and specifications are the property of M/A-COM Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.	APPD BY <u>SIR</u>	<u>5/14/69</u>	<b>AMP</b> TITLE <u>OSM FLANGE MOUNT JACK RECEPTACLE STRAIGHT TERMINAL</u>			
			.XXX = in XX.X = mm (REF)	USE ASS'Y PROCEDURE	NO. AP. <u>N/A</u>	SIZE <u>B</u>	CODE IDENT NO. <u>26805</u>	<u>2052-1352-02</u>	REV <u>01<sub>3</sub></u>
						SCALE <u>4:1</u>			SHEET 1 OF 1

CUSTOMER DRAWING AMP PART # 1052552-1 SHEET 1 OF 1 REV A

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)