



- 1 HOUSING MATERIAL: THERMOPLASTIC UL94 V-0, RoHS COMPLIANT.
- 2 CONTACT MATERIAL: HIGH CONDUCTIVITY COPPER ALLOY.
- 3 CONTACT FINISH:(D) NOBLE METAL PLATED IN CONTACT AREA OVER NICKEL UNDERPLATE ENTIRE CONTACT, AND MATTE TIN PLATE IN PIN LEADS SURFACE OVER NICKEL UNDERPLATE. LUBRICATION (MIN MATING SURFACES): SURFACE CONDITIONER AFTER PLATING.
- 4 PART MARKING, LOCATED APPROXIMATELY AS SHOWN.

ROW	D	AA	AA
	C	AA	AA
	B	AA	AA
	A	AA	AA
		1	2
POSITION			

P/N 5223172-1

CODE	MATING POST LENGTH D	LEAD LENGTH (REF)
AA	6.5	4.25

RECOMMENDED CIRCUIT PATTERN
PER IPC-D300 TYPE II, CLASS C
(COMPONENT SIDE)

6.00	1	4.25	10.00	5	11.83	3	8	5223172-1
G	F	E	C	B	A	FINISH	NO OF POSN	PART NUMBER
THIS DRAWING IS A CONTROLLED DOCUMENT.		DIMENSIONS: mm		TOLERANCES UNLESS OTHERWISE SPECIFIED:		DIN KIRAN HOLAL 23DEC11 CHK SHARPE ALEXANDER 23DEC11 APVD SHARPE ALEXANDER 23DEC11 NAME PRODUCT SPEC 108-1441 APPLICATION SPEC 114-1075 MATERIAL FINISH WEIGHT CUSTOMER DRAWING		
0 PLC ± - 1 PLC ± - 2 PLC ± 0.13[.005] 3 PLC ± - 4 PLC ± - ANGLES ± -		0.15mm 0.20mm 0.54mm		0.15mm 0.20mm 0.54mm		STC TE Connectivity ASSEMBLY, PIN, 4 ROW, PRESS-FIT, 4.25, POWER, 2mm FB SIZE A1 00779 C=5223172 SCALE 4:1 SHEET 1 OF 1 REV B		

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)