



- THIS PLUG IS DESIGNED TO CONFORM TO THE LATEST ISSUE OF MIL-C-24308
 - MAX WIRE INSUL. TO BE USED WITH THIS PLUG IS .054 DIA.
 - METAL RETENTION CLIPS ARE INCLUDED IN INSERTS
 - PACKAGE MARKED M 24308/4-332F
 - THIS PLUG WILL ACCEPT SIZE 22 PIN CONTACT M 24308/13 OR AMP # 204370
- AMP PART NO. MARKED ON CONNECTOR REPRESENTS KIT NUMBER WITH CONTACTS
 UL/CSA DESIGNATION MARKED IN THIS AREA.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DIN C.C.THOMAS 12-4-87		TE Connectivity	
DIMENSIONS: INCHES		TOLERANCES UNLESS OTHERWISE SPECIFIED:			
0 PL ± - 1 PL ± - 2 PL ± - 3 PL ± 0.005 4 PL ± - ANGLES ± 0°30'		APVD F.C.BALLEW III 1-25-88 PRODUCT SPEC APPLICATION SPEC WEIGHT CUSTOMER DRAWING		NAME AMPLIMITE PLUG FOR PIN CONTACTS HI-DENSITY D CONNECTOR SIZE4, 62 POSN., SERIES 90 WITH FLOAT BUSHINGS SIZE A1 CAGE CODE 00779 DRAWING NO. C=204531 SCALE 4:1 SHEET 1 OF 1 REV R	

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)