



DESIGNED FOR USE WITH RD178 & 196 DBLE BRD	
CABLE ENTRY DIAMETER MINIMUM	
HOUSING	.037
SLEEVE	.109
CONTACT	.023

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
01 <sub>1</sub>	REDRAWN ON CAD ECN 94-0561 <i>Ref</i>	1/6/95	<i>Ref</i> 1/6/95
02 <sub>0</sub>	REVISED; ECN 98-0022	1/21/98	<i>Ref</i>

HOUSING	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	GOLD PLATE PER MIL-G-45204
CAP		
COUPLING NUT		
DIELECTRIC	PTFE FLUOROCARBON PER ASTM-D-1457	N/A
CENTER CONTACT	BERYLLIUM COPPER PER QQ-C-530, ASTM B196, B197	GOLD PLATE PER MIL-G-45204
RETAINING RING	BERYLLIUM COPPER PER QQ-C-530, ASTM B196, B197	N/A
GASKET	SILICONE RUBBER PER ZZ-R-765	N/A
FERRULE	SOFT COPPER ALLOY	GOLD PLATE PER MIL-G-45204
SHRINK TUBING	HEAT SHRINKABLE POLYOLEFIN COMPOUND MIL-I-23053/5	N/A

COMPONENT	MATERIAL	FINISH
-----------	----------	--------

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES FRAC. ± 1/64 DEC. ± .005 ANGLES ± 1°	DRAWN BY P. DEFAZIO	DATE 4/27/88	M/A-COM a Division of AMP Incorporated 140 Fourth Avenue Waltham, MA 02154-7577
	CHECKED BY KCM	4/29/88	
	APPD BY		

NOTES:  
1. CAPTURED CENTER CONTACT

These drawings and specifications are the property of M/A COM Interconnect Div. and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.	USE ASSY PROCEDURE	TITLE OSSM RIGHT ANGLE CABLE PLUG-CRIMP ATTACHMENT		
	NO. A.P. 408-04771 (10-058)	SIZE B	CODE IDENT NO. 26805	1037-5035-18
		SCALE 4:1		REV 02 <sub>0</sub>

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)