



SECTION Y-Y  
LOADED HSG  
SCALE 4:1  
(FOR REF ONLY)

- ① HOUSING WILL ACCOMODATE FLEXIBLE FLAT CABLE .050 OR .062 WIDE CONDUCTORS (CABLE .015 MAX THK) AND/OR #22-32 AWG WIRE WITH INSULATION RANGE OF .045 TO .069 DIA.
- ② MOLDED "AMP" TRADEMARK, IN THIS AREA
- ③ PART NO. AND DATE CODE TO BE LASER MARKED
- ④ DETENTS: 6,8,10,12 & 18 POSN,(1) DETENT LOCATED AS FOLLOWS:  
6 & 8 POSN-  $\phi$  OF THRID CIRCUIT FROM RIGHT  
10 & 12 POSN-  $\phi$  OF FOURTH CIRCUIT FROM RIGHT  
18 POSN-  $\phi$  OF SIXTH CIRCUIT FROM RIGHT  
20 POSN & ABOVE- (2) DETENTS LOCATED AS SHOWN
- ⑤ CAVITY IDENT NO. TO BE LASER MARKED (SEE TABLE)
- ⑥ INDICATES POSITION 1, SURFACE TEXTURE CONTRAST'S WITH REST OF HOUSING
- ⑦ THIS HOUSING WILL MATE WITH FFC PIN HOUSING
- ⑧ OBSOLETE PART NUMBER
- ⑨ SUPERSEDED BY AS MOLDED PART NUMBER.
- ⑩ GLASS-FILLED NYLON, BLACK, UL V-0.
- ⑪ OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

|             |                      |                    |       |       |       |    |             |
|-------------|----------------------|--------------------|-------|-------|-------|----|-------------|
| ⑧ 4-88179-1 | 12-15-22             | 2-5-10             | 1.350 | 1.234 | 1.140 | 22 | ⑧ 4-88179-2 |
| ⑧ 3-88179-9 |                      |                    | .650  | .534  | .440  | 8  | ⑧ 4-88179-0 |
| ⑧ 3-88179-7 | 16-20-25-30          | 2-5-10-14          | 1.750 | 1.634 | 1.540 | 30 | ⑧ 3-88179-8 |
| ⑧ 3-88179-5 | 18-25-30-34          | 2-5-10-16          | 1.950 | 1.834 | 1.740 | 34 | ⑧ 3-88179-6 |
| ① 3-88179-3 | 7-12                 | 2-5                | .850  | .734  | .640  | 12 | ⑧ 3-88179-4 |
| ⑧ 3-88179-1 | 4-6                  | 2                  | .550  | .434  | .340  | 6  | ⑧ 3-88179-2 |
| ⑧ 2-88179-9 | 6-10                 | 2-4                | .750  | .634  | .540  | 10 | ⑧ 3-88179-0 |
| ⑧ 2-88179-7 |                      |                    | 3.750 | 3.634 | 3.540 | 70 | ⑧ 2-88179-8 |
| ⑧ 2-88179-5 |                      |                    | 3.150 | 3.034 | 2.940 | 58 | ⑧ 2-88179-6 |
| ⑧ 2-88179-3 | 23-25-30-35-40-44    | 2-5-10-15-20-21    | 2.450 | 2.334 | 2.240 | 44 | ⑧ 2-88179-4 |
| ⑧ 2-88179-1 | 21-25-30-35-40       | 2-5-10-15-19       | 2.250 | 2.134 | 2.040 | 40 | ⑧ 2-88179-2 |
| ⑧ 1-88179-9 | 19-25-30-36          | 2-5-10-17          | 2.050 | 1.934 | 1.840 | 36 | ① 2-88179-0 |
| ⑧ 1-88179-7 |                      |                    | 1.650 | 1.534 | 1.440 | 28 | ⑧ 1-88179-8 |
| ⑧ 1-88179-5 | 14-20-26             | 2-5-12             | 1.550 | 1.434 | 1.340 | 26 | ① 1-88179-6 |
| ① 1-88179-3 | 13-20-24             | 2-5-11             | 1.450 | 1.334 | 1.240 | 24 | ⑧ 1-88179-4 |
| ① 1-88179-1 | 26-30-35-40-45-50    | 2-5-10-15-20-24    | 2.750 | 2.634 | 2.540 | 50 | ⑧ 1-88179-2 |
| ① 88179-9   | 10-15-18             | 2-5-8              | 1.150 | 1.034 | .940  | 18 | ⑧ 1-88179-0 |
| ⑧ 88179-7   | 34-40-45-50-55-60-66 | 2-5-10-15-20-25-32 | 3.550 | 3.434 | 3.340 | 66 | ① 88179-8   |
| ⑧ 88179-3   | 20-25-30-35-38       | 2-5-10-15-18       | 2.150 | 2.034 | 1.940 | 38 | ⑧ 88179-6   |
| ① 88179-2   | 11-15-20             | 2-5-9              | 1.250 | 1.134 | 1.040 | 20 | ⑧ 88179-5   |
| ⑧ 88179-1   |                      |                    | 3.250 | 3.134 | 3.040 | 60 | ⑧ 88179-4   |

|  |                          |  |   |  |   |             |                       |
|--|--------------------------|--|---|--|---|-------------|-----------------------|
| LASER MARKED PART NUMBER               | FAR SIDE CAVITY POSN NO. | NEAR SIDE STAMPED                      | C | B  | A | NO OF POS'N | AS MOLDED PART NUMBER |
| THIS DRAWING IS A CONTROLLED DOCUMENT. |                          | DIN KATE HELM 11/07/88                 |   | STE TE Connectivity                        |   |             |                       |
| DIMENSIONS: INCHES                     |                          | TOLERANCES UNLESS OTHERWISE SPECIFIED: |   | HOUSING,RCPT,DBL ROW WITH DETENTS,.100 CL. |   |             |                       |
| 0 PLC ± -                              |                          | 1 PLC ± -                              |   | PRODUCT SPEC                               |   |             |                       |
| 2 PLC ± -                              |                          | 3 PLC ± .005                           |   | APPLICATION SPEC                           |   |             |                       |
| 4 PLC ± -                              |                          | ANGLES ± -                             |   | SIZE CAGE CODE DRAWING NO                  |   |             |                       |
| MATERIAL                               |                          | FINISH                                 |   | WEIGHT                                     |   |             |                       |
| ⑩                                      |                          | -                                      |   | A1 00779 C=88179                           |   |             |                       |
| CUSTOMER DRAWING                       |                          | SCALE 3:1                              |   | SHEET 1 OF 1                               |   | REV AR3     |                       |

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)