

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

| P | LTR | DESCRIPTION | DATE | DWN | APVD |
|---|-----|-----------------|-----------|-----|------|
| | A | INITIAL RELEASE | 11MAY2015 | DL | CW |
| | B | ECR-20-010477 | 28DEC2020 | BS | CW |
| | B1 | ECR-22-149504 | 15AUG2022 | RG | CW |

PG/M

(68)

78.5

(123.8)

(97.9)

SCALE 1:2

NOTES:

1. TECHNICAL CHARACTERISTICS:
 BODY MATERIAL: DIE CAST ALUMINIUM ALLOY
 SURFACE TREATMENT: POWDER-COATED, GRAY
 DEGREE OF PROTECTION: IP65 (MATED)

注释:

1. 技术参数:
 主体材料: 铝合金
 表面处理: 粉末喷涂, 灰色
 防护等级: IP65(配合)

49.7

66

75.5

8

16

| | | |
|----------------------|---------------------------|------|
| T1739320129-000 | H32A-TBF-PG29 | PG29 |
| T1739320121-000 | H32A-TBF-PG21 | PG21 |
| T1739320132-000 | H32A-TBF-M32 | M32 |
| ASSEMBLY PART NUMBER | ASSEMBLY PART DESCRIPTION | PG/M |

| DIMENSIONS: | | TOLERANCES UNLESS OTHERWISE SPECIFIED: | | DWN | | CHK | | APVD | | PRODUCT SPEC | | APPLICATION SPEC | | WEIGHT | | CUSTOMER DRAWING | | | |
|-------------|----|--|----|-----------|----------|------------|------------|-----------|----------|--------------|---------------|------------------|-----|-----------------|---|------------------|-----------|------------|---------------|
| mm | | | | 11MAY2015 | | 11MAY2015 | | 11MAY2015 | | 108-137010 | | 114-137010 | | - | | - | | | |
| 0 PLC | ±- | 1 PLC | ±- | DAVID LI | DAVID LI | CHRIS WANG | CHRIS WANG | XU XIANG | XU XIANG | NAME | H32A-TBF-PG/M | | STE | TE Connectivity | | SIZE | CAGE CODE | DRAWING NO | RESTRICTED TO |
| 2 PLC | ±- | 3 PLC | ±- | | | | | | | | | | | A3 | - | ©-T17393201XX000 | | | |
| 4 PLC | ±- | ANGLES | ±- | | | | | | | | | | | | | SCALE | SHEET | OF | REV |
| FINISH | ±- | | | | | | | | | | | | | | | 3:4 | 1 | 1 | B1 |

1470-19 (3/13)

Downloaded From Onevac.com

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)