

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS					
GP	00	P	LTR	DESCRIPTION	DATE	DWN	APVD
		B		REVISED PER ECO-14-011808	12AUG2014	AP	SB

Top view dimensions: 2.729±.015 (total length), 2.500 (inner length), 2.182 (pin array length), 10° TYP (fillet angle), .494±.015 (total width), .329 (pin array width), 2X Ø.120 (mounting holes), 1-19 and 20-37 (pin positions), GROUNDING INDENTS (pointing to indentations), MATING FACE (pointing to top surface).

Side view dimensions: .432 MAX (height), .459±.015 (height), 2.295 MAX (length).

Dimensions: .230±.006 (height), .039±.010 (height), .050±.020 (height), .462 MAX (height).

- CONNECTOR ACCEPTS SIZE 20 DF PIN CONTACTS, RETENTION TINES ARE AN INTEGRAL PART OF INSERT.
- CONNECTOR COMPLIES WITH 108-40005 WHERE APPLICABLE.
- MOLDED PARTS: GLASS-FILLED PBT OR GLASS-FILLED NYLON, UL94V-0 RATED. COLOR: BLACK.
- SHELL MATERIAL: STEEL PER ASTM A109.
- SHELL FINISH: TIN PLATE OVER COPPER UNDERPLATE.

747568-3
PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN C. VALENTINE 18NOV2009		
DIMENSIONS: INCHES		CHK C. ROHDE 18NOV2009		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD C. ROHDE 18NOV2009	NAME	
0 PLC ± -		PRODUCT SPEC	PLUG ASSEMBLY, SIZE 4, 37 POSN, HDP-20, AMPLIMITE FOR SHIELDING HARDWARE	
1 PLC ± -		APPLICATION SPEC	SIZE	RESTRICTED TO
2 PLC ± -			A2	
3 PLC ± .005			CAGE CODE	
4 PLC ± -			00779	
ANGLES ± 0° 30'			DRAWING NO	
FINISH		WEIGHT	C=747568	
SEE NOTES		CUSTOMER DRAWING	SCALE	REV
			NTS	B

1471-9 (3/11) Downloaded From Onevac.com

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)