





THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS					
J	-	P	LTR	DESCRIPTION	DATE	DWN	APVD
		D1		REVISED PER ECR-15-012855	19OCT2015	NK	GJ




1 使用端子型番：172781,172782

2 一般公差：±0.4

1 APPLICABLE CONTACT: 172781,172782

2 GENERAL TOLERANCE: ±0.4

OBSOLETE	-15	30.8	12	24			1-	-5
	12	24.8	11	22			1-	-2
OBSOLETE	-10	20.8	9	18			1-	-0
OBSOLETE	-9	18.8	8	16				-9
	8	16.8	7	14				-8
	7	14.8	6	12				-7
	6	12.8	5	10				-6
	5	10.8	4	8				-5
	4	8.8	3	6				-4
	3	6.8	2	4				-3
	2	4.8	1	2	NATURAL (自然色)			172890-2
極数	寸法			色調		型番		
POS	DIMENSION			COLOR		P/N		

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	J.SATO	15NOV2007	 TE Connectivity											
DIMENSIONS: 単位: 耗 mm		CHK	S.MANABE	15NOV2007												
TOLERANCES UNLESS OTHERWISE SPECIFIED: 一般公差		APVD	S.MANABE	15NOV2007												
<table border="1"> <tr> <td>0 PLC</td> <td>±</td> </tr> <tr> <td>1 PLC</td> <td>±</td> </tr> <tr> <td>2 PLC</td> <td>±</td> </tr> <tr> <td>3 PLC</td> <td>±</td> </tr> <tr> <td>4 PLC</td> <td>±</td> </tr> <tr> <td>ANGLES</td> <td>±</td> </tr> </table>		0 PLC	±	1 PLC		±	2 PLC	±	3 PLC	±	4 PLC	±	ANGLES	±	NAME	名称
0 PLC	±															
1 PLC	±															
2 PLC	±															
3 PLC	±															
4 PLC	±															
ANGLES	±															
MATERIAL 材料		PRODUCT SPEC		HEADER HOUSING												
66ナイロン (UL94V-0)		製品規格		LOW PROFILE MINI AMP-IN, 2MM PITCH												
66NYLON (UL94V-0)		取付適用規格		108-5163												
FINISH 仕上		WEIGHT		114-5062												
		SIZE	A3	CAGE CODE	00779											
		DRAWING NO	G=172890		RESTRICTED TO											
		CUSTOMER DRAWING		SCALE	10:1											
				SHEET	1 OF 1											
				REV	D1											

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)