



1. THIS PLUG WILL MATE WITH ANY 78 POSN., SIZE 5 RECEPTACLE IN AMPLIMITE SERIES.
2. MAXIMUM WIRE INSULATION TO BE USED WITH THIS PLUG IS .054 DIA.
3. SST RETENTION CLIPS ARE INCLUDED IN INSERTS.
4. THIS PLUG IS DESIGNED TO CONFORM TO THE LATEST ISSUE OF MIL-C-24308.
5. CONNECTOR SUPPLIED WITHOUT CONTACTS; SHOWN FOR ILLUSTRATION ONLY.
6. THIS PLUG WILL ACCEPT SIZE 22 DM PIN CONTACT M39029/58-22-22D OR ANY AMP SIZE 22 DF PIN CONTACT.

UL/CSA DESIGNATION STAMPED IN THIS AREA.

PRELIMINARY NOT RELEASED FOR PRODUCTION	ZINC	AS SHOWN	445012-2
	CADIMUM	AS SHOWN	445012-1
	SHELL FINISH	DESCRIPTION	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DIN	D. POWERS	10-13-92
DIMENSIONS: INCHES		CHK	R. GILLMAN	10-13-92
TOLERANCES UNLESS OTHERWISE SPECIFIED:		NAME		
0 PLC	± .005	PRODUCT SPEC		
1 PLC	± .005	APPLICATION SPEC		
2 PLC	± .005	SIZE		
3 PLC	± .005	CAGE CODE		
4 PLC	± .005	DRAWING NO		
ANGLES	± .005	RESTRICTED TO		
MATERIAL SEE CALLOUT	FINISH SEE CALLOUT	WEIGHT	A1 00779 445012	
CUSTOMER DRAWING		SCALE	1:1	SHEET 1 OF 1

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)