



- 1 FOR USE WITH .093 MINIMUM THICK PRINTED CIRCUIT BOARD. REFER TO APPLICATION SPECIFICATION FOR PRINTED CIRCUIT BOARD LAYOUT DIMENSIONS AND FINISH RECOMMENDATIONS.
- 2 FLAME RETARDANT, 94V-0 RATED, GLASS FILLED, NYLON OR POLYESTER, COLOR: BLACK.
- 3 COPPER ALLOY
- 4 BRASS
- 5 GOLD FLASH IN MATING AREA. .000100 MINIMUM TIN OR TIN-LEAD ON COMPLIANT PIN. ALL OVER .000050 MINIMUM NICKEL.
- 6 .000030 MINIMUM GOLD IN MATING AREA. .000100 MINIMUM TIN OR TIN-LEAD ON COMPLIANT PIN. ALL OVER .000050 MINIMUM NICKEL. OR GOLD FLASH OVER PALLADIUM NICKEL. .000030 MINIMUM TOTAL IN MATING AREA. .000100 MINIMUM TIN OR TIN-LEAD ON COMPLIANT PIN. ALL OVER .000050 MINIMUM NICKEL.
- 7 SCREWLOCKS: NICKEL PLATED.
- 8 SCREWLOCKS MUST WITHSTAND 4 INCH-LBS TORQUE AND 20 LBS PULL OUT FORCE FROM MATING FACE SIDE.
- 9 SCREWLOCKS MUST BE FLUSH TO .015 BELOW MATING FACE.

OBSOLETE	5	745458-2
	5	745458-1
	CONTACT FINISH	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT. DIMENSIONING AND TOLERANCING PER ASME Y14.5M-2009		DMN W. LENKER 5-31-88	APVD S. WELDON 6-1-88	
DIMENSIONS: INCHES		TOLERANCES UNLESS OTHERWISE SPECIFIED:		NAME
0 PLC	± -	PRODUCT SPEC		RECEPTACLE ASSEMBLY, SIZE 3, 25 POSITION, WITH ACTION PIN CONTACTS & SCREWLOCKS.
1 PLC	± -	APPLICATION SPEC		108-40014
2 PLC	± -	SIZE		114-40026
3 PLC	± .005	CAGE CODE		00779
4 PLC	± -	DRAWING NO		745458
ANGLES	± -	RESTRICTED TO		
MATERIAL	FINISH	WEIGHT	SCALE	SHEET
2 3 4	1		4:1	1 OF 1
CUSTOMER DRAWING		REV H		

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)