



- ① CUSTOMER PART NO., 00779, DATE CODE, PART NO. AND AMP MARKED THIS SIDE.
- ② HOUSING MAT'L: POLYPHENYLENE SULFIDE, GST-40F PER MIL-M-24519.
- ③ CONTACT MAT'L: BRASS PER QQ-B-626.
- ④ CONTACT FINISH: .000030" [0.00127] GOLD OVER .000050" [0.00127] NICKEL IN CONTACT AREA.
- ⑤ CONTACT FINISH: .000100" [0.00254] TIN-LEAD OVER .000050" [0.00127] NICKEL
- ⑥ LETTERS INDICATING OUTSIDE ROWS AND NUMBERS INDICATING END CAVITIES (ROW C ONLY) MARKED THIS SURFACE.
- ⑦ NUMBERS INDICATING EVERY FIVE CAVITIES MARKED, BOTH SIDES.
- ⑧ LINES INDICATING EVERY FIVE CAVITIES MARKED ON MATING FACE EXCEPT END CAVITIES STARTING FROM POSN. #1.
- ⑨ CONTACT FINISH: .000100" [0.00254] TIN OVER .000050" [0.00127] NICKEL

⑨	-	120	180	5-448008-1
⑧	(774443-4)	120	180	448008-1
	CUSTOMER P/N	NO. OF CONTACTS	NO. OF POSN	PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN T. ALEXANDER 8-5-92	Tyco Electronics Corporation Harrisburg, Pa 17105-3608	
DIMENSIONS: INCHES		CHK D. MILLER 3-30-93	APVD	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		PRODUCT SPEC		
0 PLC ± -		APPLICATION SPEC		
1 PLC ± -		SIZE		
2 PLC ± -		CAGE CODE		
3 PLC ± .005 [0.13]		DRAWING NO		
4 PLC ± -		RESTRICTED TO		
ANGLES ± -		A1 00779 C=448008		
FINISH		WEIGHT		
② ③		CUSTOMER DRAWING		
④ ⑤ ⑨		SCALE 4:1 SHEET 1 OF 1 REV B		

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)