



THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION  
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC		DIST		REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD				
AD	00	G	REVISED PER ECO-14-000066	27JUN2014	NK	MM			



- 1 THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND THE HOUSING.
- 2 POINT OF MEASUREMENT FOR PLATING THICKNESS.
- 3 FOR ACTIVE POSITION SIZES 4 AND ABOVE, POSTS WILL BE SELECTIVELY SWAGED TO PROVIDE CONNECTOR RETENTION TO THE PC BOARD UNTIL SOLDERED. FOR POSITION SIZE 2, POSTS WILL BE KINKED.(SEE TABLE FOR RETENTION FEATURE LOCATION).
- 4 BREAKAWAY NOTCH ANGLE CAN BE ORIENTED TO THE RIGHT (AS SHOWN) OR TO THE LEFT.
- 5 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI.



RECOMMENDED HOLE LAYOUT

5	OBSOLETE	1,2,39,40	1,2,39,40	3.984	3.900	39	80	2-104353-0
		1,2,29,30	1,2,29,30	2.984	2.900	29	60	1-104353-9
		1,2,24,25	1,2,24,25	2.484	2.400	24	50	1-104353-8
		1,2,19,20	1,2,19,20	1.984	1.900	19	40	1-104353-7
		1,2,16,17	1,2,16,17	1.684	1.600	16	34	1-104353-6
5	OBSOLETE	1,2,14,15	1,2,14,15	1.484	1.400	14	30	1-104353-5
		1,2,13,14	1,2,13,14	1.384	1.300	13	28	1-104353-4
		1,2,12,13	1,2,12,13	1.284	1.200	12	26	1-104353-3
		1,2,11,12	1,2,11,12	1.184	1.100	11	24	1-104353-2
		1,2,10,11	1,2,10,11	1.084	1.000	10	22	1-104353-1
5	OBSOLETE	1,2,9,10	1,2,9,10	.984	.900	9	20	1-104353-0
		1,2,8,9	1,2,8,9	.884	.800	8	18	104353-9
		1,2,7,8	1,2,7,8	.784	.700	7	16	104353-8
		1,2,6,7	1,2,6,7	.684	.600	6	14	104353-7
		1,2,5,6	1,2,5,6	.584	.500	5	12	104353-6
5	OBSOLETE	1,2,4,5	1,2,4,5	.484	.400	4	10	104353-5
		1,2,3,4	1,2,3,4	.384	.300	3	8	104353-4
		1,2,3	1,2,3	.284	.200	2	6	104353-3
		1,2	1,2	.184	.100	1	4	104353-2
		1	1	.084	-	-	2	104353-1
		ROW N	ROW M	C	B	A	NO OF POSN	ASSEMBLY PART NUMBER
		HOLD-DOWN POST CONFIG LOCATION						

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN M. PASTAL 04FEB88	<b>STE</b> TE Connectivity														
		CHK R. FEIDT 09FEB88															
		APVD R. FEIDT 09FEB88	NAME														
DIMENSIONS: INCHES		TOLERANCES UNLESS OTHERWISE SPECIFIED:		PRODUCT SPEC													
<table border="1"> <tr><td>0 PLC</td><td>± -</td></tr> <tr><td>1 PLC</td><td>± -</td></tr> <tr><td>2 PLC</td><td>± -</td></tr> <tr><td>3 PLC</td><td>± .005</td></tr> <tr><td>4 PLC</td><td>± -</td></tr> <tr><td>ANGLES</td><td>± -</td></tr> </table>		0 PLC	± -	1 PLC	± -	2 PLC	± -	3 PLC	± .005	4 PLC	± -	ANGLES	± -	APPLICATION SPEC		WEIGHT -	
0 PLC	± -																
1 PLC	± -																
2 PLC	± -																
3 PLC	± .005																
4 PLC	± -																
ANGLES	± -																
MATERIAL HOUSING: FLAME RETARDANT THERMOPLASTIC. COLOR:BLACK. POSTS: COPPER ALLOY		FINISH: POSTS: 000030 GOLD ON THE CONTACT AREA .000100-.000200 MATTE TIN-LEAD ON THE SOLDER TAIL. ALL OVER .000050 NICKEL.		SCALE 4:1													
		CUSTOMER DRAWING		SHEET 1 of 1													

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)