



PCB Layout

NOTES :

- △ MATERIALS AND FINISH:
  - HOUSING: PA66
  - CONTACTS: BRASS, FINISH: TIN OVER NICKEL UNDERPLATE
- 2. MUST COMPLY WITH DIRECTIVE 2002/95/EC (RoHS)
- 3. WIRE TYPES AND SIZES ACCEPTED
- WIRE RANGE: 14AWG~28AWG.
- STRIP LENGTH: 10mm
- 4. PACKAGED IN TRAY.
- 5. CURRENT RATING: 16amp AC300V.
- 6. OPERATION TEMPERATURE: -40°C TO +105°C
- 7. THIS PART NO. IS THE SAME STRUCTURE AS THE SERIES: 2834076
- THE DATASHEET AND MORE DETAILS PLEASE FOLLOW THE SERIES: 2834076

REV	DATE	BY	APP'D	DESCRIPTION
1				

REV	DATE	BY	APP'D	DESCRIPTION
1				

NO. OF POSITIONS	PART NO
8 POSN	2834076-7
7 POSN	2834076-6
6 POSN	2834076-5
5 POSN	2834076-4
4 POSN	2834076-3
3 POSN	2834076-2
2 POSN	2834076-1

THIS DRAWING IS A CONTROLLED DOCUMENT.

GEORGE FU 23NOV2015

SHI LANG 23NOV2015

PRODUCT CODE: 109-137146

APPROVAL DATE: 11-4-137146

VERSION: -

CUSTOMER DRAWING

SCALE: 1:1

SHEET 1 OF 1

REV A

5.00mm 45° Entry Screwless Connector

C-2834076

REGISTERED TO

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)