



REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
01 ₁	RELEASED	3/10/97	<i>RAC</i>

ELECTRICAL	MECHANICAL	ENVIRONMENTAL	COMPONENT	MATERIAL	FINISH
Nominal Impedance (Ohms) <u>50</u>	Interface Dimensions MIL-STD-348A, Fig. <u>310-2</u>	Temperature Rating <u>-65 TO +165°C</u>	HOUSING	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	PASSIVATE PER QQ-P-35
Frequency Range (GHz) DC to <u>18</u>	Recommended Mating	Vibration MIL-STD-202, Method 204, Condition B	DIELECTRIC	PTFE FLUOROCARBON PER ASTM-D-1457	N/A
Volt Rating (VRMS MAX) @ Sea Level <u>335</u>	Torque <u>7-10 IN-LBS</u>	Shock MIL-STD-202, Method 213, Condition I	CENTER CONTACT	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204
VSWR <u>1.05 + .005 f(GHz)</u>	Mating Characteristics:	Thermal Shock MIL-STD-202, Method 107, Condition B, Except High Temp +85°C	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES		
Insertion Loss (dB MAX) <u>.2dB</u>	Insertion (MAX Lbs) <u>4.0</u>	Moisture Resistance MIL-STD-202, Method 106	FRAC. ± 1/64	DEC. ± .005	ANGLES ± 1°
RF Leakage (dB MIN) <u>90dB</u>	Withdrawal (MIN Oz) <u>1.0</u>	Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray	DRAWN BY <u>TM WAGNER</u> DATE <u>10/17/97</u>		
Corona, 70,000 Ft (VRMS MIN) <u>250</u>	Force to Engage and Disengage (In-Lbs MAX) <u>2.0</u>		CHECKED BY _____		
Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level <u>1,000</u>	Center Contact Captivation		APPD BY _____		
Contact Resistance (Milliohms MAX)	Axial (Lbs) <u>6.0</u>		AMP Incorporated		
Center Contact <u>3.0</u>	Radial (In-Oz) <u>N/A</u>		140 Fourth Avenue		
Outer Contact <u>2.0</u>	Cable Retention		Waltham, MA 02451-7599		
Cable to Housing <u>N/A</u>	Axial Force (Lbs) <u>N/A</u>		TITLE <u>"SMA" STRAIGHT 2 HOLE FLG MOUNT JACK ACCEPT .036 DIA PIN</u>		
RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) <u>670</u>	Torque (In-Oz) <u>N/A</u>		SIZE <u>B</u> CODE IDENT NO. <u>26805</u> 2052-3359-02 REV <u>01₁</u>		
LR.(Megohms MIN) <u>10,000</u>	Weight (Grams) <u>TBD</u>		SCALE <u>6:1</u> SHEET <u>1 OF 1</u>		
		.XXX = in XX.X = mm (REF)	USE ASS'Y PROCEDURE		
			NO. A.P. <u>N/A</u>		

CUSTOMER DRAWING AMP PART # 1052646-1 SHEET 1 OF 1 REV A

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)