



LOC		DIST		REVISIONS			
GP	00	REV	DATE	BY	CHK	APPV	
B1	REVISED PER ECO-11-004835		11MAR11	RK	HMR		



- 1 HOUSING: FLAME RETARDANT, 94V-0 RATED, THERMOPLASTIC;
COLOR: BLACK
SHELL: CARBON STEEL
CONTACTS: BRASS
INSERTS: BRASS
SCREWLOCKS: ZINC
- 2 SHELL: .000200 MIN TIN OVER .000100 MIN COPPER.
INSERTS: UNPLATED.
SCREWLOCKS: CLEAR CHROMATE.
CONTACTS: GOLD PLATED FOR A LENGTH OF .150 MIN FROM MATING END, .000030 MIN GOLD IN MATED AREA, .000100 MIN TIN ON OPPOSITE END, ALL OVER .000050 MIN NICKEL.
-OR-
GOLD FLASH OVER PALLADIUM NICKEL PLATED FOR A LENGTH OF .150 MIN FROM MATING END, .000030 MIN PALLADIUM NICKEL IN MATED AREA, .000100 MIN TIN ON OPPOSITE END, ALL OVER .000050 MIN NICKEL.
- 3 DATUMS AND BASIC DIMENSIONS ESTABLISHED BY CUSTOMER.
- 4 .110 MAX IN SHELL TAB CLINCH AREAS.



RECOMMENDED PC BOARD MOUNTING DIMENSIONS

W/FEMALE SCREWLOCKS	.170	1-5747872-6
W/THREADED INSERTS	.125	5747872-8
W/Ø.120	.170	5747872-4
HARDWARE	A	PART NO

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES	TOLERANCES UNLESS OTHERWISE SPECIFIED:	DIN 20SEP05	NAME
0 PLC ± -	1 PLC ± -	20SEP05	PLUG ASSEMBLY, SIZE 2, 15 POS., VERTICAL, .026 DIA POSTS, FRONT SHELL, AMPLIMITE HD-20
2 PLC ± -	3 PLC ± .005	APPROVED	SIZE
4 PLC ± -	ANGLES ± -	M. WALMSLEY	A1
		108-40025	DRAWING NO
		114-40023	00779
MATERIAL	FINISH	WEIGHT	RESTRICTED TO
			5747872
CUSTOMER DRAWING		SCALE 4:1	SHEET 1 OF 1 REV B1

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)

[>>点击查看相关商品](#)