



RECOMMENDED HOLE LAYOUT

- △1 THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND THE HOUSING.
- △2 POINT OF MEASUREMENT FOR PLATING THICKNESS.
- △3 0.000381[.000015] GOLD IN CONTACT AREA, 0.00254[.000100]-0.00504[.000200] MATTE TIN-LEAD ON SOLDER TAIL, ALL OVER 0.00127[.000050] NICKEL.
- △4 RETENTION FEATURES ON SOLDER TAILS, LOCATED AT MANUFACTURERS OPTION.
- △5 $\text{Ø}0.020\text{M}$ FOR KINKED TAILS.
- 6 0.000381[.000015] GOLD IN CONTACT AREA, 0.00254[.000100]-0.00504[.000200] MATTE TIN ON SOLDER TAIL, ALL OVER 0.00127[.000050] NICKEL.
- 7 HIGH TEMPERATURE CONFIGURATION.
- △8 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI.

| | | | | | | | | | | | |
|----|--------------------------|----|---------|--------------|-----------------|---------------|-------------------|----|------------|------------|----------------------|
| △8 | OBSOLETE | △7 | △6 | 5,6,18,21,22 | 21 | 32.61 [1.284] | 12 | 26 | 5-104721-7 | | |
| △8 | OBSOLETE | △7 | △6 | 5 | 7 | 19.91 [.784] | 7 | 8 | 5-104721-6 | | |
| △8 | OBSOLETE | △7 | △6 | 2 | 6 | 17.37 [.684] | 6 | 7 | 5-104721-4 | | |
| | | △7 | △6 | 2 | 3 | 9.75 [.384] | 3 | 4 | 5-104721-3 | | |
| | | △7 | △6 | 4 | 5 | 14.83 [.584] | 5 | 6 | 5-104721-2 | | |
| △8 | OBSOLETE | △7 | △6 | 2 | 4 | 12.29 [.484] | 4 | 5 | 5-104721-1 | | |
| △8 | OBSOLETE | | △3 | 5,6,18,21,22 | 21 | 32.61 [1.284] | 12 | 26 | 104721-7 | | |
| △8 | OBSOLETE | | △3 | 5 | 7 | 19.91 [.784] | 7 | 8 | 104721-6 | | |
| △8 | OBSOLETE | | △3 | 4,8,10 | 9 | 30.07 [1.184] | 11 | 12 | 104721-5 | | |
| △8 | OBSOLETE | | △3 | 2 | 6 | 17.37 [.684] | 6 | 7 | 104721-4 | | |
| | SUPERCEDED BY 5-104721-3 | | △3 | 2 | 3 | 9.75 [.384] | 3 | 4 | 104721-3 | | |
| | SUPERCEDED BY 5-104721-2 | | △3 | 4 | 5 | 14.83 [.584] | 5 | 6 | 104721-2 | | |
| △8 | OBSOLETE | | △3 | 2 | 4 | 12.29 [.484] | 4 | 5 | 104721-1 | | |
| | REMARKS | | PLATING | | POST NO OMITTED | | NO OF ACTIVE POSN | B | A | NO OF POSN | ASSEMBLY PART NUMBER |

THIS DRAWING IS A CONTROLLED DOCUMENT. DTN KATE HELM 07/09/90. CHK R FEJDT 7/10/90. APVD

STE TE Connectivity

NAME: HDR ASSY, BREAKAWAY, MOD II, WITH RETENTION FEATURE

PRODUCT SPEC: --- APPLICATION SPEC: ---

SIZE: A1 CASE CODE: --- DRAWING NO: 00779 C=104721

RESTRICTED TO: ---

MATERIAL: HDGNS: FLAME RETARDANT THERMOPLASTIC COLOR: BLACK POSTS: COPPER ALLOY FINISH: SEE TABLE WEIGHT: ---

CUSTOMER DRAWING SCALE: 4:1 SHEET: 1 OF 1 REV: S

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)