

4

3

2

1

© - TE Connectivity. All Rights Reserved.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
G		REV PER ECO 20-015601	11-9-20	CT	PD

- 1 WIRE INSULATION: .367-417 DIA
- 2 THE TONGUE RADIUS FEATURE IS NOT A TOOLING CONTROLLED DIMENSION AND MAY NOT BE A TRUE RADIUS.
- 3 .020 FLASH PERMITTED ON WIRE BARREL DUE TO IMPACTING
- 4 STAMP "AMP 2 AL 13-78" SIZE AND LOCATION APPROX AS SHOWN
5. STUD HOLES SHALL HAVE NO DETACHABLE BURRS THAT WOULD RESULT IN EXPOSED BASE METAL

5/16 OR M8	.328	BODY: COPPER ASTM-B187 ANNEALED TIN PL PER ASTM B-545 .000150 MIN THK INSERT & FUNNEL: BRASS ASTM B36 NICKEL PL SAE AMS QQ-N-290A, DATED JULY 2000, .000100 MIN THK	696838-2
3/8	.390	BODY: COPPER ASTM-B187 ANNEALED TIN PL PER ASTM B-545 .000150 MIN THK INSERT & FUNNEL: BRASS ASTM B36 NICKEL PL SAE AMS QQ-N-290A, DATED JULY 2000, .000100 MIN THK	696838-1
DIM B	DIM A	MATERIAL & FINISH	PART NO

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN JR RUTH 13OCT05			
DIMENSIONS: INCHES		CHK MJ SPICER 13OCT05			
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD MJ SPICER 13OCT05	NAME WIRE TERMINAL, RING TONGUE SEALED COPALUM WIRE SIZE: 2 AL		
0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± .008 4 PLC ± - ANGLES ± -		PRODUCT SPEC APPLICATION SPEC	SIZE A2	CAGE CODE 00779	DRAWING NO C-696838
MATERIAL SEE TABLE		FINISH SEE TABLE	WEIGHT 0.000000	RESTRICTED TO -	SCALE 3:1
		CUSTOMER DRAWING		SHEET 1 of 1	REV G

1471-9 (1/15)

Downloaded From Onevac.com

696838

B

A

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)