



- NOTES :
- ▲ MATERIALS AND FINISH:  
 - HOUSING: PA66  
 - CONTACTS: BRASS, FINISH: TIN OVER NICKEL UNDERPLATE
2. MUST COMPLY WITH DIRECTIVE 2002/95/EC (ROHS)
3. WIRE TYPES AND SIZES ACCEPTED  
 WIRE RANGE: 20AWG~28AWG.  
 STRIP LENGTH: 5.5mm~6.5mm
4. PACKAGED IN TRAY.
5. CURRENT RATING: 4Amp AC150V.
6. OPERATION TEMPERATURE: -40°C TO +105°C
7. THIS PART NO. IS THE SAME STRUCTURE AS THE SERIES: 2834084  
 THE DATASHEET AND MORE DETAILS PLEASE FOLLOW THE SERIES: 2834084

LDC		JUST		REVISIONS		
P	LTN	DESCRIPTION	DATE	DM	AP/3	
A		FIRST VERSION	08DEC2015	CF	SM	

④	WIRE PROTECTOR
③	CONTACT
②	COVER
①	HOUSING
21.50	8 POSN 2834084-7
19.00	7 POSN 2834084-6
16.50	6 POSN 2834084-5
14.00	5 POSN 2834084-4
11.50	4 POSN 2834084-3
9.00	3 POSN 2834084-2
6.50	2 POSN 2834084-1

THIS DRAWING IS A CONTROLLED DOCUMENT.

ST  
 TE Connectivity

NAME: 2.5 45Entry Screwless Connector

DATE: 08DEC2015

REV: A

SIZE: A2

CODE: 00779

SCALE: 1:1

SHEET: 1 OF 1

REV: A

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)