

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL	18MAR2015	DW	CW
	B	ECR-15-018270	07DEC2015	DW	CW
	C	ECR-21-111798	23SEP2021	WQR	CW


NOTES:

- TECHNICAL CHARACTERISTICS:
INSULATION MATERIAL: PC
RATED VOLTAGE: 1000V
RATED CURRENT: 100A
INSULATION RESISTANCE: $\geq 400M\Omega$
RATED IMPULSE VOLTAGE: 8KV
POLLUTION DEGREE: 3
FLAMMABILITY: UL94V-0
MATING CYCLES: 500 CYCLES
OPERATION TEMPERATURE: $-40^{\circ}C \sim +125^{\circ}C$
WIRE RANGE: $10.0mm^2 \sim 35.0mm^2$
CONTACT TYPE: CRIMP CONTACT
- CONTACT NEED TO BE ORDERED SEPARATELY.
(ORDER No. REFER TO DRAWING: T20500020XX000)

注释:

- 技术参数:
绝缘材料: PC
额定电压: 1000V
额定电流: 100A
绝缘电阻: $\geq 400M\Omega$
脉冲电压: 8KV
污染等级: 3
阻燃等级: UL94V-0
插拔次数: 500次
工作温度: $-40^{\circ}C \sim +125^{\circ}C$
接线范围: $10.0mm^2 \sim 35.0mm^2$
接线类型: 冷压接
- 端子需要单独订购.
(订货号参考图面: T20500020XX000)

HMN-D2-FC	T2111028201-000
DESCRIPTION	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	18MAR2015	 TE Connectivity	
DIMENSIONS:		CHK	18MAR2015		
mm		APVD	18MAR2015		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		NAME	NAME		
0 PLC	±-	PRODUCT SPEC	108-137058	HMN-D2-FC	
1 PLC	±-	APPLICATION SPEC	114-137058	SIZE	CAGE CODE
2 PLC	±-	WEIGHT	-	A3	00779
3 PLC	±-	Customer Drawing	SCALE	DRAWING NO	
4 PLC	±-		1:1	T2111028201000	
ANGLES	±-		SHEET	RESTRICTED TO	
FINISH	-		1 OF 1	-	
MATERIAL	-		REV	C	
	-				

1470-19 (3/13)

Downloaded From Oneyac.com

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)