# SPECIFICATION CONTROL DRAWING THREE CONDUCTOR CABLE, JACKETED, GENERAL PURPOSE, 600 VOLT Date 12-3-05 Revision A

This specification sheet forms a part of the latest issue of Raychem Specification 55A



#### ADDITIONAL REQUIREMENTS

SOLDERABILITY (Quality Conformance): 95% (minimum) coverage per MIL-STD-202, Method 208 (1 hour steam aging)

Except as specified above, this construction shall meet all the requirements of Raychem Specification Sheet 55A4831 for AWG sizes 24 through 10.

#### PART NUMBER:

The 55A7299 part number shall be modified to include the applicable AWG size followed by color code designators with a slash separating the component wire colors and a dash separating the component wire colors from the jacket color. Colors shown do not necessarily reflect the sequence of manufacturing.

1/ Example: AWG 20, black, brown and red component wires; white jacket: 55A7299-20-0/1/2-9

Users should evaluate the suitability of this product for their application. Specifications are subject to change without notice.

Tyco Electronics also reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to Buyer.

1/ COLORS AND COLOR CODE DESIGNATORS SHALL BE IN ACCORDANCE WITH MIL-STD-681. HOWEVER, DUE TO LENGTH LIMITATIONS OF THE RAYCHEM PART NUMBER, AN ALTERNATIVE COLOR CODE MAY REPLACE MIL-STD-681 COLOR CODE DESIGNATORS. (EXAMPLE: "901/902..." MAY BE REPLACED BY "AXXX".) OTHER CODES AND SUFFIXES MAY BE ADDED TO THE PART NUMBER, AS NECESSARY, TO CAPTURE ANY ADDITIONAL REQUIREMENTS IMPOSED BY THE PURCHASE ORDER.

Page 1 of 1

Title

DIMENSIONS ARE IN INCHES AND, UNLESS OTHERWISE DESIGNATED, ARE NOMINAL

**tyco**Electronics

Raychem Wire & Cable 501 Oakside Avenue Redwood City, CA 94063-3800 Phone: 1-800-227-8816 Fax: 1-650-361-6297

### 单击下面可查看定价,库存,交付和生命周期等信息

## >>TE Connectivity(泰科)